is an issue for you, there exists the Symfony PSR-7 Bridge https://symfony.com/doc/current/components/psr7.html or you can use something ultra-lightweight, such as https://github.com/Nyholm/psr7.

By using symfony/http-foundation in your project, the entire request can be easily encapsulated with one line of code. It can be installed with Composer (which had a brief mention in the autoloading section of Chapter 6, "Object Fundamentals"). Visit https://getcomposer.org to get started. (Composer is also well covered in *PHP 8 Objects, Patterns, and Practice*.)

```
$ composer require symfony/http-foundation
```

The Symfony\Component\HttpFoundation\Request class instance then exposes all of the facets of the protocol through various properties and methods. Make sure your autoloading boilerplate is in place (Composer is a great help with this), then interacting with HTTP requests is as simple as doing things like this:

```
use Symfony\Component\HttpFoundation\Request;

$request = Request::createFromGlobals();

$request->cookies; // access cookies
$request->query; // access query params
$request->getMethod(); // HTTP request method
// etc.
```

HttpFoundation also provides a nice OOP API for building responses…

```
use Symfony\Component\HttpFoundation\Response;

$response = new Response(
    $responseBody,
    Response::HTTP_OK,
    ['Content-Type:', 'text/html']
);
$response->send();
```

… and even different response classes for common cases such as returning JSON-encoded data…