The simplest job HTML does is to structure text. This is achieved by wrapping the text you want your users to see in certain tags to form *block-level* elements. "Block-level" means that the content inside the element starts on a new line in the browser and occupies the full available width of the parent element, pushing subsequent content onto a new line. Examples of block-level elements:

Table 11-8. *Some HTML block-level elements*

`<div>`	Division (generic) container
`<p>`	Paragraph
`<h1>` to `<h6>`	Heading text (six levels)
`<ul>`, `<ol>`, `<li>`	Unordered and Ordered lists, and their list elements
`<form>`	HTML form
`<header>`, `<footer>`, `<nav>` `<article>`, `<aside>`, `<main>`	HTML5 semantic elements
`<main>`, `<section>`	HTML5 main content, and (grouped) related content

Let's see some in action. Launch a `cli-server` PHP server (see the "HTTP" section earlier in the chapter for full details)…

```
$ docker run -it --rm -p 8080:8080 \
  -v "$PWD":/usr/src/myapp \
  -w /usr/src/myapp php:8.4-cli \
  php -S 0.0.0.0:8080
PHP 8.4.6 Development Server (http://0.0.0.0:8080) started
```

… and create the following HTML document (save it as something like block_level.html):

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8" />
    <title>Block level element demo</title>
  </head>
```