... and we can even use the old `DOMXPath` utility class (which behaves exactly the same as `Dom\XPath`):

```
$xpath = new DOMXPath($dom);
$results = $xpath->query('//footer');
print "Found {$results->length} matching node(s)" . PHP_EOL;
var_dump($results[0]->textContent);
```

```
Output:
Found 1 matching node(s)
string(11) "Page footer"
```

So, all is not lost if you're stuck on PHP 8.3 (or earlier). It would be nice if we could get rid of those initialization errors though, especially if our HTML is chock-full of new elements. Luckily there are a couple of ways to do it:

```
// ... $html5 heredoc as before
libxml_use_internal_errors(true);
$dom = new DOMDocument();
$dom->loadHTML($html5);
print "Document loaded." . PHP_EOL;
var_dump(libxml_get_errors());
```

```
Output:
Document loaded.
array(3) {
  [0]=>
  object(LibXMLError)#2 (6) {
    ["level"]=>
    ...
    ["message"]=>
    string(19) "Tag header invalid
    ...
```

`libxml_use_internal_errors(true)` will suppress error emission and instead store them in an internal array, which can be accessed with `libxml_get_errors()`. Re-enable normal error behavior by calling `libxml_use_internal_errors(false)`. Alternatively, you can suppress errors completely when loading the document...