or browser history, none of which exist in your PHP script. In fact, the `querySelector()` and `querySelectorAll()` DOM methods in PHP don't have full support for the full spectrum of CSS selectors exactly for this reason. The pseudo-class most likely to be relevant to you is `:has`, which is a nifty hack that allows for (in a roundabout way) the selection of parents or ancestors, but others aren't supported and will trigger a fatal error. For example, `:visited` isn't supported…

```
$visitedLinks = $dom->querySelectorAll('main a:visited');
```

```
Output:
PHP Fatal error:  Uncaught DOMException: Invalid selector (Selectors. Not
supported: visited)
```

… because it requires a browser with history. This is the case for many other pseudo-classes, so test your selector expressions with care.

You can combine simple selectors to form compound selectors, which are just a sequence of simple selectors without a combinator (a single space character is one of the combinators in CSS, so compound selectors do not contain spaces). If a compound selector contains a type (element name) or universal (asterisk) selector, it must come first and must be the only instance. Here are some examples:

Table 11-20. *CSS compound selectors*

`.green`	Any element with a `green` class
`*.green`	Equivalent to `.green`
`div.green`	Any `div` element with a `green` class
`p[id]`	Any `p` element possessing an `id` attribute
`p#special.green.large`	A `p` element with `id` "special" with both `green` AND `large` classes

And finally, complex selectors use combinators to join simple and compound selectors together. You can think of combinators as functioning like the axes of XPath: a space in CSS is `descendant::`, a `>` is `child::`, and so on. The CSS combinators are: