Ah, but wait! What's up with that `meta` tag? HTML `meta` tags are self-closing (because they never contain child elements), so why did we pick one up? If you look back to when the DOM was created via `$dom = Dom\HTMLDocument::createFromString(...);` you'll notice the `HTML_NO_DEFAULT_NS` constant was supplied as an argument. This made our XPath code slightly easier (no need to register the default namespace, etc.), but it introduces an issue. Hopefully you'll recall me saying that a lack of correct namespace introduces issues to `HTMLDocument`; this is one of them. Without the HTML5 schema, the rules for writing the markup, the parser isn't aware that `meta`, `img` et al. don't need closing tags and "helpfully" puts one in for you. If you intend to generate HTML5 markup from your DOM, it will need the correct default namespace:

```
$dom = Dom\HTMLDocument::createFromString($html5);
print $dom->saveHTML();
```

```
Output:
<!DOCTYPE html><html><head>
  <meta charset="utf-8">
```

Don't be concerned about the lack of forward slash on the closing chevron of `meta`; the HTML5 spec doesn't require them, and the Lexbor library that powers all of this is sticking to the standards.

Manipulating `class`

Going back to our newly rearranged DOM, now that we've juggled the order of the `p` elements, we might want to adjust the classes – a fairly common job when processing a DOM. With PHP 8.4, the `dom` extension provides some useful utilities for interacting with an element's `class` attribute. The `Dom\Element::classList` property is an instance of `Dom\TokenList`…

```
var_dump($lastPara->classList);
Output:
object(Dom\TokenList)#6 (2) {
  ["length"]=>
  int(2)
  ["value"]=>
  string(12) "small  blah "
}
```