```
laravel new todo-app
cd todo-app
php artisan serve
```

Your app should now be running at `http://127.0.0.1:8000`. Then, close the server with `Ctrl+C`.

You can open the project in your favorite code editor, such as Visual Studio Code:

```
code .
```

10.5.5.2 Step 2: Configure SQLite Database

Laravel 12 **uses SQLite by default**, but we need to ensure the correct setup.

1. View an SQLite database file, `database.sqlite`, in the `database` folder.
2. Open `.env` and update the database settings:

   ```
   DB_CONNECTION=sqlite
   DB_DATABASE=database/database.sqlite
   ```

3. Clear the config cache:

   ```
   php artisan config:clear
   ```

10.5.5.3 Step 3: Create a Migration for the `todos` Table

We will create a migration file to define the `todos` table structure.

Run the migration command:

```
php artisan make:migration create_todos_table
```

You will see a new file in the `database/migrations/` directory. Open the generated file in `database/migrations/YYYY_MM_DD_create_todos_table.php` and update it:

```
<?php
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration {
    public function up()
    {
        Schema::create('todos', function (Blueprint $table) {
            $table->id();
            $table->string('task');
            $table->boolean('completed')->default(false);
            $table->timestamps();
        });
    }
```