```
                'updated_at' => Carbon::now()
            ],
            [
                'task' => 'Buy fruits',
                'completed' => false,
                'created_at' => Carbon::now(),
                'updated_at' => Carbon::now()
            ],
            [
                'task' => 'Complete Laravel project',
                'completed' => true,
                'created_at' => Carbon::now(),
                'updated_at' => Carbon::now()
            ],
        ]);
    }
}
```

This code defines a seeder that inserts three dummy tasks into the `todos` table.

Seed the database:

```
php artisan db:seed --class=TodoSeeder
```

Now you can see the `todos` table with dummy data in the SQLite database, `database/database.sqlite`.

10.5.5.5 Step 5: Create the Todo Model

We will create a model for the `todos` table to interact with it using Eloquent ORM.

Run:

```
php artisan make:model Todo
```

This will create a new model file in the `app/Models` directory. Open the generated file in `app/Models/Todo.php` and update it:

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Todo extends Model
{
    use HasFactory;

    protected $fillable = ['task', 'completed'];
}
```

Save the file. This code defines the `Todo` model and specifies that the `task` and `completed` attributes are mass assignable.