```
{
    use HasFactory;

    protected $fillable = ['user_id', 'title', 'content'];

    public function user()
    {
        return $this->belongsTo(User::class);
    }

    public function tags()
    {
        return $this->belongsToMany(Tag::class);
    }
}
```

This code defines the `Post` model and specifies that the `user_id`, `title`, and `content` attributes are mass assignable. The `user()` method defines the **inverse** of the **One-to-Many relationship** with the `User` model. The `tags()` method defines the **Many-to-Many relationship** with the `Tag` model.

Edit `app/Models/Tag.php`:

```
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use App\Models\Post;

class Tag extends Model
{
    use HasFactory;

    protected $fillable = ['name'];

    public function posts()
    {
        return $this->belongsToMany(Post::class);
    }
}
```

This code defines the `Tag` model and specifies that the `name` attribute is mass assignable. The `posts()` method defines the **Many-to-Many relationship** with the `Post` model.

Save all the files. This code defines the models and their relationships for the `users`, `profiles`, `posts`, and `tags` tables.

10.7.4.5 Step 5: Create Seeders

We will create seeders to populate the `users`, `profiles`, `posts`, and `tags` tables with initial data.

If `database/seeders/DatabaseSeeder.php` file already exists, you can skip this step. If not, run the following command to create a seeder: