```
php artisan make:seeder DatabaseSeeder
```

This will create a new seeder file in the `database/seeders` directory. Open the generated file in `database/seeders/DatabaseSeeder.php` and update it on `run()` method:

```
use App\Models\User;
use App\Models\Profile;
use App\Models\Post;
use App\Models\Tag;

...

    public function run(): void
    {
        User::factory(10)->create();

        // create a profile for each user
        foreach (User::all() as $user) {
            $user->profile()->create([
                'bio' => 'This is a bio for user ' . $user->id,
                'website' => 'https://ilmudata.id/user/' . $user->id,
            ]);
        }

        // create posts for each user
        foreach (User::all() as $user) {
            $user->posts()->create([
                'title' => 'Post Title for user ' . $user->id,
                'content' => 'This is the content of the post for user ' . $user->id,
            ]);
        }

        // create tags and associate them with posts
        foreach (Post::all() as $post) {
            $tag = Tag::create(['name' => 'Tag for post ' . $post->id]);
            $post->tags()->attach($tag->id);
        }
    }
```

Seed the database:

```
php artisan db:seed
```

This code creates a user, a profile for that user, a post for that user, and a tag for that post. It also attaches the tag to the post using the `attach()` method.

You can check the SQLite database to confirm that the tables have been populated with initial data.

You can open the SQLite database file in DBeaver and check the `users`, `profiles`, `posts`, and `tags` tables to confirm that the data has been populated.

10.7.4.6 Step 6: Create Controllers