By default, Laravel uses SQLite for local development. You can see this in the `.env` file.

```
DB_CONNECTION=sqlite
```

You also see database file `database.sqlite` in the `database` directory. If you missed this, you can create a SQLite database file by performing the following command:

```
php artisan migrate
```

11.7.4.3 Step 3: Create Migrations for Users, Products, and Orders

We will create migrations for two tables: `products`, and `orders`. These tables will store information about products, and orders respectively.

Create the migrations:

```
php artisan make:migration create_products_table
php artisan make:migration create_orders_table
```

Laravel 12 already has a `users` table by default. You can use that table for this exercise.

Open the newly created migration files in the `database/migrations` directory and modify them to create the `products` and `orders` tables. The files will be named something like `xxxx_xx_xx_xxxxxx_create_products_table.php` and `xxxx_xx_xx_xxxxxx_create_orders_table.php`.

Open `xxxx_xx_xx_xxxxxx_create_products_table.php` and modify it:

```
Schema::create('products', function (Blueprint $table) {
    $table->id();
    $table->string('name');
    $table->decimal('price', 8, 2);
    $table->timestamps();
});
```

Open `xxxx_xx_xx_xxxxxx_create_orders_table.php` and modify it:

```
Schema::create('orders', function (Blueprint $table) {
    $table->id();
    $table->foreignId('user_id')->constrained();
    $table->foreignId('product_id')->constrained();
    $table->integer('quantity');
    $table->timestamps();
});
```