Save the files and run the migrations to create the `products` and `orders` tables:

```
php artisan migrate
```

You can verify that the tables have been created by checking the database file or using a database management tool.

11.7.4.4 Step 4: Seed the Database

To populate the tables with sample data, we will create a seeder for the `users`, `products`, and `orders` tables.

```
php artisan make:seeder SampleSeeder
```

This will create a new seeder file in the `database/seeders` directory. Open the newly created file and add the following code to seed the tables. Edit `database/seeders/SampleSeeder.php`:

```
use Illuminate\Support\Facades\DB;

public function run(): void
{
    DB::table('users')->insert([
        ['name' => 'William', 'email' => 'william@example.com', 'password' => bcrypt('passw
        ['name' => 'Nia', 'email' => 'nia@example.com', 'password' => bcrypt('password123')
    ]);

    DB::table('products')->insert([
        ['name' => 'Laptop', 'price' => 1000],
        ['name' => 'Phone', 'price' => 600],
    ]);

    DB::table('orders')->insert([
        ['user_id' => 1, 'product_id' => 1, 'quantity' => 2],
        ['user_id' => 1, 'product_id' => 2, 'quantity' => 1],
        ['user_id' => 2, 'product_id' => 1, 'quantity' => 1],
    ]);
}
```

Save the file. This seeder will insert sample data into the `users`, `products`, and `orders` tables.

Run the seeder:

```
php artisan db:seed --class=SampleSeeder
```

You can verify that the tables have been populated by checking the database file or using a database management tool.