```
    Route::delete('/products/{product}', [ProductController::class, 'destroy'])->name('proc
});
```

This sets up the routes for the `ProductController` methods. The routes are protected by authentication middleware, ensuring that only authenticated users can access them.

15.6.4.6 Step 6: Set Up React Frontend

We will create a simple React component to manage products. Create a folder named `products` inside `resources/js/pages` and create the following files:

- `index.tsx`
- `create.tsx`
- `edit.tsx`
- `show.tsx`

Create `resources/js/pages/products/index.tsx` and replace with the following code:

```
import AppLayout from '@/layouts/app-layout'
import { Head, Link, usePage } from '@inertiajs/react'
import { type BreadcrumbItem } from '@/types'

const breadcrumbs: BreadcrumbItem[] = [
  { title: 'Products', href: '/products' },
]

export default function ProductIndex({ products }: { products: any[] }) {
    const { flash } = usePage().props as { flash?: { success?: string } }

  return (
    <AppLayout breadcrumbs={breadcrumbs}>
      <Head title="Products" />

      <div className="container mx-auto p-4">
        {flash?.success && <div className="bg-green-100 text-green-800 p-2 mb-4 rounded">
{flash.success}</div>}

        <div className="flex justify-between items-center mb-4">
          <h1 className="text-2xl font-bold">Products</h1>
          <Link
            href="/products/create"
            className="bg-blue-500 text-white px-4 py-2 rounded hover:bg-blue-600"
          >
            Create
          </Link>
        </div>

        <div className="overflow-x-auto">
            <table className="min-w-full bg-white dark:bg-gray-800 shadow rounded-lg text-
sm">
                <thead>
                <tr className="bg-gray-200 dark:bg-gray-700 text-left text-gray-800
dark:text-gray-100">
                    <th className="py-2 px-4 border-b border-gray-300 dark:border-gray-
```