```
    <ul>
        <li><strong>Interface Binding:</strong> {{ $interfaceMsg }}</li>
        <li><strong>Standard Binding (Transient):</strong> {{ $standardMsg }}</li>
        <li><strong>Singleton Binding:</strong> {{ $singletonMsg }}</li>
    </ul>
</body>
</html>
```

5.11.4.7 Step 7: Run the App

After completing the above steps, run the app using the built-in server:

```
php artisan serve
```

Visit in your browser:

- `http://127.0.0.1:8000/message`

Expected Output:

- **StandardMessageService** (transient) should show a different timestamp on every request
- **SingletonMessageService** will also show a new timestamp on every request (since `php artisan serve` restarts the container every time)

5.11.4.8 To simulate actual singleton behavior:

Modify the controller to resolve the singleton **twice in the same request**:

```
public function show(Request $request)
{
    $standard = app('standard.message');
    $singleton = app('singleton.message');

    $first = app('singleton.message')->getMessage();
    $second = app('singleton.message')->getMessage();

    return view('message', [
        'interfaceMsg' => $this->service->getMessage(),
        'standardMsg' => $standard->getMessage(),
        'singletonMsg' => $singleton->getMessage(),
        'first' => $first,
        'second' => $second,
    ]);
}
```

In your Blade view (`resources/views/message.blade.php`):

```
<body>
    <h1>Laravel 12 DI Demo</h1>
```