You may give middleware aliases in your application's **app/Http/Kernel.php** file for convenience. The middleware that comes with Laravel is listed in the class's **$middlewareAliases** field by default. You are free to add your own middleware and give it whatever alias you like to this list:

```
// Within App\Http\Kernel class…
protected $middlewareAliases = [
  'auth' => \App\Http\Middleware\Authenticate::class,
  'auth.basic' =>
  \Illuminate\Auth\Middleware\AuthenticateWithBasicAuth::class,
  'bindings' =>
  \Illuminate\Routing\Middleware\SubstituteBindings::class,
  'cache.headers' =>
  \Illuminate\Http\Middleware\SetCacheHeaders::class,
  'allowed' => \Illuminate\Auth\Middleware\Authorize::class,
  'guest' =>
  \App\Http\Middleware\RedirectIfAuthenticated::class,
  'signed' =>
  \Illuminate\Routing\Middleware\ValidateSignature::class,
  'throttle' =>
  \Illuminate\Routing\Middleware\ThrottleRequests::class,
  'verified' =>
  \Illuminate\Auth\Middleware\EnsureEmailIsVerified::class,
];
```

When adding middleware to routes, you can utilize the middleware alias that has been specified in the HTTP kernel.

```
Route::get('/EmployeeProfile', function () {
  // Code Logic
})->middleware('auth');
```

## Middleware Groups

To make it simpler to attach middleware to routes, you might occasionally wish to aggregate several middleware under a single key. The **$middlewareGroups** property of your HTTP kernel may be used to do this.

The web and API middleware groups that Laravel pre-defines contain common middleware that you might wish to use on your **web** and **API** routes.