routes/api.php files in your application right out of the box.

Sorting Middleware

Rarely, you could require your middleware to run in a precise sequence, but you wouldn't have control over the order in which they appear when they are assigned to the route. In this situation, the **$middlewarePriority** property of your **app/Http/Kernel.php** file may be used to indicate your middleware priority.

Your HTTP kernel may not, by default, have this attribute. You can duplicate its default definition if it doesn't already exist:

```
/**
 * The priority-sorted list of middleware.
 *
 * This forces non-global middleware to always be in the given
 order.
 *
 * @var string[]
 */
protected $middlewarePriority = [
 \Illuminate\Foundation\Http\Middleware\HandlePrecognitiveReque
 sts::class,
 \Illuminate\Cookie\Middleware\EncryptCookies::class,
 \Illuminate\Session\Middleware\StartSession::class,
 \Illuminate\View\Middleware\ShareErrorsFromSession::class,
 \Illuminate\Contracts\Auth\Middleware\AuthenticatesRequests::c
 lass,
 \Illuminate\Routing\Middleware\ThrottleRequests::class,
 \Illuminate\Routing\Middleware\ThrottleRequestsWithRedis::clas
 s,
 \Illuminate\Contracts\Session\Middleware\AuthenticatesSessions
 ::class,
 \Illuminate\Routing\Middleware\SubstituteBindings::class,
 \Illuminate\Auth\Middleware\Authorize::class,
];
```

Source: https://laravel.com/docs/