```
  Passport::personalAccessTokensExpireIn(now()->addMonths(6));
 }
```

Overriding Default Models

By creating your own model and expanding the matching Passport model, you are able to expand the internal models that Passport uses:

```
use Laravel\Passport\Client as PassportClient;
class Client extends PassportClient
{
  // Code Logic
}
```

Once your model has been defined, you can use the **`Laravel\Passport\Passport`** class to tell Passport to utilize your custom model. Generally, the **`App\Providers\AuthServiceProvider`** class **`boot`** function in your application is where you should tell Passport about your custom models:

```
use App\Models\Passport\AuthCode;
use App\Models\Passport\Client;
use App\Models\Passport\PersonalAccessClient;
use App\Models\Passport\RefreshToken;
use App\Models\Passport\Token;
public function boot(): void
{
  Passport::useTokenModel(Token::class);
  Passport::useRefreshTokenModel(RefreshToken::class);
  Passport::useAuthCodeModel(AuthCode::class);
  Passport::useClientModel(Client::class);
  Passport::usePersonalAccessClientModel(PersonalAccessClient::c
  lass);
}
```

Overriding Routes

There may be occasions when you want to alter the Passport-defined routes. In order to accomplish this, you must first add **`Passport::ignoreRoutes`** to the **`register`** function of your application's **`AppServiceProvider`** in order to ignore the routes registered by Passport: