Use the **`make:test`** Artisan command to generate a new test case. Tests will by default be stored in the **`tests/Feature`** directory:

```
php artisan make:test SampleTest
```

To create a test within the **`tests/Unit`** folder directory, use the **`–unit`** option when executing the **`make:test`** command:

```
php artisan make:test SampleTest –unit
```

You may provide the make command the **`--pest`** option if you want to construct a PHP test called **`make:test`** command:

```
php artisan make:test SampleTest --pest
php artisan make:test SampleTest --unit --pest
```

After the test has been produced, you may use PHPUnit to define test methods as usual. Use the **`vendor/bin/phpunit`** or **`php artisan test`** command from your terminal to begin running your tests:

```
<?php
namespace Tests\Unit;
use PHPUnit\Framework\TestCase;
class Sampletest extends TestCase
{
 public function test_basic_test(): void
 {
  $this->assertTrue(true);
  //Logic of the test case
 }
}
```

Running Tests

In order to run a test, use the `phpunit command`:

```
./vendor/bin/phpunit
```

To run your tests, you can also use the `test Artisan` command in addition to the `phpunit` command. Verbose test results are provided by the Artisan test runner to facilitate development and debugging:

```
php artisan test
```

Any arguments that can be passed to the `phpunit` command may also be passed to the `Artisan test` command: