```
php artisan test --testsuite=Feature --stop-on-failure
```

Parallel Execution of Tests

Typically, PHPUnit and Laravel execute tests sequentially within a single process. Yet, opting for concurrent test execution across multiple processes can substantially reduce the overall testing time. To initiate this process, the initial step involves installing the brianium/paratest Composer package as a `dev` dependency. Subsequently, you can utilize the test Artisan command with the `--parallel` option enabled to implement this approach.

```
composer require brianium/paratest --dev
php artisan test –-parallel
```

Laravel will by default start as many processes as your computer's available CPU cores. However, you may use the `--processes` option to change the number of processes:

```
php artisan test --parallel --processes=2
```

Laravel handles the generation and migration of a test database for each parallel test process, provided a primary database connection has been configured. Each process is assigned a unique process token appended to the test databases. For example, if there are two concurrent test processes, Laravel will create and utilize test databases, including **`your_db_test_1`** and **`your_db_test_2`**.

By default, the test databases remain persistent, potentially carrying over data from previous test runs when invoking the **`test`** Artisan command. However, you can use the **`--recreate-databases`** option to recreate these databases as needed.

```
php artisan test --parallel --recreate-databases
```

In certain cases, it becomes necessary to configure specific resources for your application's tests, ensuring smooth accessibility for multiple test processes.

Using the **`ParallelTesting`** facade, you can define code to be executed during the **`setUp`** and **`tearDown`** of a process or test case. The specified closures receive the **`$token`** and **`$testCase`** variables, which respectively hold the process token and the active test case.

```
<?php
namespace App\Providers;
```