`APP_ENV`	Environment name
`APP_DEBUG`	FALSE
`APP_LOG_LEVEL`	Debug
`APP_URL`	Vanity domain, or custom domain if exists
`ASSET_URL`	CloudFront
`AWS_BUCKET`	Storage resource if exists
`BROADCAST_DRIVER`	Pusher
`CACHE_DRIVER`	DynamoDB, or cache (Redis) resource if exists
`DB_*`	Database (MySQL, Postgresql, etc) resource if exists
`DYNAMODB_CACHE_TABLE`	**vapor_cache**
`FILESYSTEM_DISK`	S3
`FILESYSTEM_DRIVER`	S3
`FILESYSTEM_CLOUD`	S3
`LOG_CHANNEL`	Stderr
`MAIL_DRIVER`	LOG, but SES for environments with the name **production**
`MAIL_MAILER`	LOG, but SES for environments with the name **production**
`MAIL_FROM_ADDRESS`	**hello@example.com** or **hello@custom-domain.com** if exists
`MAIL_FROM_NAME`	**your_project_name**
`MIX_URL`	CloudFront
`QUEUE_CONNECTION`	SQS
`SCHEDULE_CACHE_DRIVER`	DynamoDB
`SESSION_DRIVER`	Cookie

Table 10.1: *Environment Variables injected by Vapor on the environment*

When you manage your environment with Vapor CLI or Vapor UI, you will not see these environment variables, and any variables you explicitly set will override Vapor's automatically injected variables.

Deployment