You may generate a certificate using the domain screen in the Vapor UI or the **`cert`** CLI command:

```
vapor cert example.com
```

The validity status of your certificates may be seen using the Vapor UI or by using the **`cert:list`** command CLI command list:

```
vapor cert:list example.com
```

If you wish to destroy an old certificate that is no longer associated with an environment, use the domain information page in the Vapor UI or the **`cert:delete`** CLI command. Vapor will offer you to pick the individual certificate you wish to destroy for the provided domain when you execute the command:

```
vapor cert:delete example.com
```

Add Domain to Environment

Once your domain has a valid SSL certificate, you may use the **`domain`** configuration option in your application's **`vapor.yml`** file to connect it to your environment. You do not need to add the www subdomain when linking a domain to an environment:

```
id: 3
name: vapor-laravel-app
environments:
 production:
  domain: example.com
  build:
   - 'composer install --no-dev'
```

Vapor will automatically set up the environment to handle requests from this domain upon deployment. However, because of the nature of AWS CloudFront, custom domains sometimes take 30-45 minutes to completely activate. So, don't be concerned if your custom domain isn't instantly available after deployment.

Vapor lets you associate many domains with a single project. Make sure you have a valid certificate for each of the domains before proceeding. Then, change the **`vapor.yml`** file in your application to add each domain:

```
id: 3
name: vapor-laravel-app
```