```
  Route::get('city/{id}', function (string $name, string $id) {
    // Code Logic
  });
});
```

Route Prefixes

Each route in the group may be prefixed with a specific URI using the **`prefix`** method. For instance, you might wish to append **`admin:`** to the beginning of every route URI in the group.

```
Route::prefix('hr')->group(function () {
  Route::get('/employees', function () {
    // Matches The "/hr/employees" URL
  });
});
```

In order to prefix each route in the group, which also has a valid URL – the Laravel in-built method can be used. The method **`prefix`** helps achieve this functionality. A good practice is to make use of **`admin`** and prefix the group with the same.

We will make sure to include the trailing because the given string is prefixed to the route name exactly as it is specified. An element of the prefix:

```
Route::name('admin.')->group(function () {
  Route::get('/city', function () {
    // Route assigned name "admin.city"
  })->name('city');
});
```

Cross-origin Resource Sharing (CORS)

With values that you specify, Laravel may automatically reply to CORS **`OPTIONS`** HTTP requests. You may configure every CORS setting in the **`config/cors.php`** configuration file for your application.

The **`HandleCors`** middleware, which comes preinstalled in your global middleware stack, will automatically handle the **`OPTIONS`** requests. The HTTP kernel (**`App\Http\Kernel`**) of your application houses the whole global middleware stack.