Figure 3.5: *Views*

Nested Views Directories

The **`resources/views`** directory's subdirectories are another place where views can be nested. Nested views may be referred to using "dot" notation.

For instance, if your view is located at **`resources/views/admin/welcome.blade.php`**, you could return it using the following syntax from a route or controller in your application:

```
return view('admin.welcome', $data);
```

The `.` character shouldn't be used in view directory names.

First Available View

You can build the first view in an array of views by using the **`first`** method of the **`View`** facade. If your application or package permits views to be modified or replaced, this might be helpful:

```
use Illuminate\Support\Facades\View;
return View::first(['custom.playground', 'playground'], $data);
```

Use the **`View`** facade to check whether a view is available. If the view is present, the **`exists`** method will return **`true`**.

```
use Illuminate\Support\Facades\View;
if (View::exists('emails.employee')) {
  // Code Logic
}
```

Data and Views

The data to be given in this way should be an array containing key/value pairs. You can use the data's keys, such as **`<?php echo $name;?>`**, to retrieve each value in your view after delivering the data to it.

You can add certain pieces of data to the view using the **`with`** method rather than sending the **`view`** helper function a whole array of data.

Before returning the view, the **`with`** method returns an instance of the view object so that you can chain additional methods:

```
return view('welcome')
```