The **@pushOnce** and **@prependOnce** directives are included for your convenience since the **@once** directive is frequently used in combination with the **@push** or **@prepend** directives:

```
@pushOnce('scripts')
  <script>
    // Custom JavaScript script
  </script>
@endPushOnce
```

Blade as Template Engines in Laravel

The straightforward yet effective templating engine that comes with Laravel is called Blade. In contrast to several PHP templating engines, Blade does not prevent you from utilizing raw PHP code in your templates,. In reality, Blade adds practically no cost to your application because all templates are converted into normal PHP code and cached until they are updated. Blade template files normally reside in the **resources/views** directory and have the **.blade.php** file extension.

Using the global **view** helper, Blade views may be retrieved from routes or controllers. Additionally, data may be provided to the Blade view via the view helper's second parameter, as explained in the documentation on views:

```
Route::get('/', function () {
  return view('welcome', ['name' => 'ABC']);
});
```

Data in Blade

By enclosing the variable in curly brackets, data that is supplied to your Blade views may be shown. Consider the following route, for instance:

```
Route::get('/', function () {
  return view('welcome', ['name' => 'ABC']);
});
```

In order to display the contents inline of the variables, use double curly brackets: **{{variable_name}}**

For the preceding example, it will be: