Lastly, we need to trigger a webhook if the transaction fails. Here's the complete `TransactionController`:

```
try {
  // Calculating VAT, etc ...

  $transaction = Transaction::create([ ... ]);

  try {
    if ($webhook = Webhook::transactionCreated($request->user())) {
      SendWebhookJob::dispatch($webhook, 'transaction_created', [
          'data' => $transaction,
      ]);
    }
  } catch (Throwable) {}

  return response([
    'data' => TransactionResource::make($transaction)
  ], Response::HTTP_CREATED);
} catch (Throwable $ex) {
  if ($webhook = Webhook::transactionFailed($request->user())) {
    SendWebhookJob::dispatch($webhook, 'transaction_failed', [
        'data' => $request->all(),
    ]);
  }

  throw $ex;
}
```

You'll have logs such as these:

id	uuid	webhook_id	payload	response_status	event	error	status	created_at	updated_at
13	9b0d132…	2	{"data": {"id": 1005, "uuid": "9b0d131e-73ec-4ac3…	404	transaction_created	HTTP request returned status co…	failed	2024-01-09 12:49:44	2024-01-09 12:49:44
14	9b0d135…	2	{"data": {"id": 1005, "uuid": "9b0d131e-73ec-4ac3…	404	transaction_created	HTTP request returned status co…	failed	2024-01-09 12:50:16	2024-01-09 12:50:16
15	9b0d136…	41	{"data": {"id": 1006, "uuid": "9b0d135f-d518-4a34…	404	transaction_created	HTTP request returned status co…	failed	2024-01-09 12:50:22	2024-01-09 12:50:22
16	9b0d138…	41	{"data": {"id": 1007, "uuid": "9b0d1389-95ef-4f3f…	200	transaction_created	NULL	succeeded	2024-01-09 12:50:49	2024-01-09 12:50:49
17	9b0d139…	41	{"data": {"id": 1006, "uuid": "9b0d135f-d518-4a34…	200	transaction_created	NULL	succeeded	2024-01-09 12:50:52	2024-01-09 12:50:52