circuit, reducing component count and speeding prototyping. It suits consumer electronics, industrial control, and portable devices needing adaptable signal processing or control functions in a small footprint.
Renesas Electronics
https://www.renesas.com/en

Flexible radar front ends


Qorvo has introduced C-band radar front-end components to improve frequency agility and power efficiency in pulsed Electronically Scanned Array (ESA) radar. The portfolio includes the QPB1055 switched Bulk Acoustic Wave (BAW) filter, QPA2311 GaN power amplifier, and QPA0018 high-power GaN amplifier. The filter enables rapid frequency switching and simpler receivers, while the amplifiers deliver efficient high-power transmission with lower thermal demands for defence radar, surveillance and radio frequency (RF) sensing.



Qorvo
https://www.qorvo.com

Tiny capacitors stabilise power in compact electronics

Murata Manufacturing has begun mass production of its LLD series of ultra-small three-terminal multilayer ceramic capacitors (MLCCs) that stabilise power delivery to high-speed ICs. Low equivalent series inductance (ESL) and shorter current paths suppress high-frequency noise and respond to rapid current changes. They occupy significantly less PCB space than earlier designs, making them suitable for smartphones, wearables, and other dense, space-constrained electronics.



Murata Manufacturing Co., Ltd
https://www.murata.com/en-us

High-power resistors speed design validation


Vishay Intertechnology has introduced four thick-film resistor sample kits to speed up design validation in high-power electronics. They cover the Sfernice D2TO20, D2TO35, DTO35 and combined DTO35/D2TO35 series, with multiple resistance values and optional PCB evaluation boards for electrical and thermal testing. The AEC-Q200-qualified, non-inductive resistors suit automotive, industrial, and power applications and cut lab setup time.



Vishay Intertechnology
https://www.vishay.com

Power inductors target lower energy loss

TAIYO YUDEN has expanded its power inductor portfolio with components that reduce energy losses in compact devices. Low DC resistance supports efficient power conversion in space-constrained designs, minimising heat and improving power delivery in smartphones, wearables, computing equipment and industrial electronics. The parts can extend battery life and improve thermal performance.




TAIYO YUDEN
https://www.yuden.co.jp/en

EMBEDDED

Faster optical links for AI networks

Nvidia and Cisco have announced the Ultra-Dense Small Form Factor Pluggable (USFP), an optical module design for AI data centre networks. It supports 400Gbps per lane, double the 200Gbps of existing modules, and adds capacity without extra switch layers. Targeting Ethernet switches and high-performance NICs, it aims to reduce power consumption, latency, and deployment costs.



Nvidia and Cisco
https://www.nvidia.com/en-in
https://www.cisco.com

A power board to simplify AI server delivery


Navitas Semiconductor, with Nvidia, has developed a 24kW power delivery board that converts 800V DC directly to 12V DC, in one stage, for next-generation AI servers. Eliminating the intermediate 50V stage cuts power losses, board space, and complexity. Using GaN power switches, it delivers high efficiency and power density close to the graphics processing units (GPUs).



Navitas Semiconductor
https://navitassemi.com/home

A compact-industrial board packing 180 TOPS of AI

IBASE Technology has introduced the IB966, a compact industrial single-board computer for high-performance edge AI, offering up to 180 TOPS. Powered by Intel Core Ultra Series 3 processors, it combines CPU, GPU, and NPU acceleration to process workloads locally. It offers high-speed networking, industrial interfaces, expandable storage, hardware security, and remote management for machine vision, smart manufacturing, transportation, medical imaging, and retail.



IBASE Technology
https://www.ibase.com.tw

Compact MPU combines Linux and real-time control

Nuvoton has introduced the NuMicro MA35D0 series of compact microprocessors (MPUs) for industrial edge computing, combining Linux application processing with real-time control. The devices integrate dual Arm Cortex-A35 cores, a Cortex-M4 core, and onboard DDR SDRAM, simplifying PCB design. Secure boot, Arm TrustZone and hardware cryptography protect systems, while Gigabit Ethernet and CAN FD target industrial gateways, automation equipment and

