```
•               // Shrink half as fast as we grow
•               CurrentScale -= (DeltaTime * 0.5f);
•           }
•           // Make sure we never drop below our starting 
size, or increase past double size.
•           CurrentScale = FMath::Clamp(CurrentScale, 1.0f, 
2.0f);
•           OurVisibleComponent->SetWorldScale3D(FVector(Curre
ntScale));
•       }
•
•       // Handle movement based on our "MoveX" and "MoveY" 
axes
•       {
•           if (!CurrentVelocity.IsZero())
•           {
•               FVector NewLocation = GetActorLocation() + 
(CurrentVelocity * DeltaTime);
•               SetActorLocation(NewLocation);
•           }
•       }
•
• }
```

8. After which bind your input

```
• // Called to bind functionality to input
• void AMyPawn::SetupPlayerInputComponent(UInputComponent* 
PlayerInputComponent)
• {
•       Super::SetupPlayerInputComponent(InputComponent);
•
•       // Respond when our "Grow" key is pressed or 
released.
•       InputComponent->BindAction("Grow", IE_Pressed, this, 
&AMyPawn::StartGrowing);
•       InputComponent->BindAction("Grow", IE_Released, this, 
&AMyPawn::StopGrowing);
•
•       // Respond every frame to the values of our two move-
ment axes, "MoveX" and "MoveY".
•       InputComponent->BindAxis("MoveX", this, 
&AMyPawn::Move_XAxis);
```