

Specifications							Photoshop filters (seconds)	Quake III (Normal) (fps)	Quake III (High): fps	Audio encoding (seconds)	ZD Content Creation index	Rating
Duron 600 MHz processor, 128 MB PC133 SDRAM, 20 GB ATA/100 hard disk, SiS 730 onboard graphics card, 52x CD-ROM drive, IDE interface, Ace 56K modem, integrated soundcard, 15-inch monitor							262.03	24.1	6	71	23.6	B-
Celeron 800 MHz processor, 64 MB PC133 SDRAM, i810 chipset based motherboard, 20 GB ATA/66 hard disk, integrated graphics card, 56x CD-ROM drive, IDE interface, integrated soundcard, 56K modem, 15-inch Microtek monitor							234.87	22.1	14.7	66	21.9	B
Celeron 700 MHz processor, 64 MB SDRAM, 810 chipset based motherboard, 20 GB ATA/66 hard disk, integrated graphics card, 52x CD-ROM drive, IDE interface, onboard soundcard, 56K modem							284	21	14.7	77	21	B
Celeron 633 MHz processor, 64 MB SDRAM, 810 chipset based motherboard, 20 GB hard disk, 52x CD-ROM drive, IDE inter- face, onboard soundcard, 15-inch monitor							318	15.8	14.6	84	19.9	B-
Pentium III 866 MHz processor, 128 MB SDRAM, 810 chipset based motherboard, 20 GB hard disk, integrated graphics card, 52x CD-ROM drive, IDE interface, onboard soundcard, 15-inch monitor							177	24.1	16.2	55	27.9	B
Pentium III 933 MHz processor, 64 MB RAM, KOB 815 E FSX chipset based motherboard, 52x CD-ROM drive, IDE interface							198.5	36.1	20	47	28.1	B
Celeron 667 MHz processor, 64 MB SDRAM, i810 chipset based motherboard, 20 GB hard disk, onboard graphics card, 52x CD-ROM drive, IDE interface, onboard soundcard, 56K modem, 15-inch monitor							273	21.3	14.7	80	20.3	B-
Celeron 800 MHz processor, 64 MB PC133 SDRAM, 810 chipset based motherboard, 20 GB ATA/66 hard disk, onboard graph- ics card, 52x CD-ROM drive, IDE interface, onboard soundcard, 15-inch monitor							257.57	15.5	Failed	71	Failed	B-
Celeron 733 MHz processor, 64 MB PC133 SDRAM, i810 chipset based motherboard, 20 GB ATA/66 hard disk, onboard graph- ics card, 52x CD-ROM, IDE interface, onboard soundcard, 56K ESS internal modem, 15-inch monitor							290.93	30.2	21.2	73	22.9	B
Celeron 733 MHz processor, 64 MB SDRAM, 20 GB hard disk, onboard graphics card, 52x CD-ROM drive, onboard soundcard, 56K modem							242	24.4	17.1	71	22.3	B-
Coppermine 1 GHz processor, 64 MB SDRAM/133, i815 chipset based motherboard, Fujitsu MPG3204AT 20 GB hard disk, inte- grated graphics card, 52x CD-ROM drive, IDE interface, onboard soundcard, 14-inch monitor							184.7	35.8	19.9	47	25.5	B
Pentium III 800 MHz processor, 128 MB SDRAM, i815 chipset based motherboard, 20 GB hard disk, onboard graphics card, 48x CD-ROM drive, onboard soundcard, 56K modem							185.73	36.5	19.9	55	28.8	B+
Pentium III 800 MHz processor, 64 MB SDRAM, SiS 630 chipset based motherboard, 10 GB ATA/66 hard disk, integrated graphics card, 52x CD-ROM drive, IDE interface, integrated soundcard, 15-inch monitor							242.33	26.6	12.3	60	Failed	B-
AMD Athlon 1 GHz processor, 256 MB RAM, ECS 266 chipset based motherboard, 20 GB ATA 100 hard disk drive, SiS 730 onboard graphics card, 52x CD-ROM drive, IDE interface, onboard soundcard, 56K modem, 17-inch monitor							150	35.1	7.8	35	29.4	B+
AMD Athlon 850 MHz processor, 128 MB PC133 SDRAM, KM-133 based motherboard, 20 GB ATA/100 hard disk drive, S3 Pro Savage onboard graphics card, 52x CD-ROM drive, IDE interface, onboard soundcard, Ace internal 56K modem, 15-inch monitor							175.2	26.3	7.8	40	30.6	B
Pentium III 900 MHz processor, 64 MB SDRAM, 810 chipset based motherboard, 20 GB ATA/66 hard disk drive, integrated graphics card, 48x CD-ROM drive, integrated soundcard, 56K modem, 15-inch monitor							212.33	27.5	18.2	51	27.6	B
Pentium 4 1.4 GHz processor, 128 MB RDRAM, 40 GB hard disk drive, TNT2 M64 32 MB graphics card, 16x DVD drive, CMI 8738 soundcard, 56K modem							273	68	21.3	37	33.1	B
Pentium III 1GHz processor, 128 MB PC133 SDRAM, 815 chipset based motherboard, 20 GB ATA/66 hard disk drive, nVidia Riva TNT2 M64 32 MB graphics card, 56x CD-ROM drive, IDE interface, integrated soundcard, 56K Dlink modem, 15-inch monitor							150.37	67.6	21.3	44	32.7	B+
Pentium 4 1.4 GHz processor, 128 MB PC 800 RDRAM, i850GB chipset based motherboard, 20 GB ATA/66 hard disk drive, TNT2 Ultra 32 MB graphics card, 52x CD-ROM drive, IDE interface, Lancer soundcard, Motorola 56K modem, 15-inch monitor							217	68.2	21.2	39	22.4	B
Intel Pentium 4 1.4 GHz processor, 128 MB PC 800 RDRAM, i850GB chipset based motherboard, 20 GB ATA/100 Quantum Fireball LCT hard disk drive, TNT2 M64 32 MB graphics card, 10x DVD drive, IDE interface, integrated soundcard, 15-inch monitor							221.7	76.5	25.1	45	26.2	B+
Intel Pentium III 933 MHz processor, 64 MB PC133 SDRAM, i815 chipset based motherboard, 20 GB ATA/100 Fujitsu MPG3204AT hard disk drive, integrated graphics card, 52x CD-ROM drive, IDE interface, onboard soundcard, 15-inch monitor							206	36.3	19.9	51	26.3	B
Pentium 4 1.4 GHz processor, 128 MB RDRAM, i850 based motherboard, 20 GB hard disk drive, S3 Savage 4 16 MB graphics card, 12x DVD drive, AC97 Audio Controller onboard soundcard, 56K modem, 17-inch monitor							2203	31.4	13.4	43	15.5	B
Pentium III 866 MHz processor, 128 MB SDRAM, Intel 815 based motherboard, 20 GB ATA/100 hard disk drive, onboard graphics card and soundcard, 56K modem							172.5	35.8	19.6	51	31.3	B+
Pentium III 1 GHz processor, 128 MB SDRAM, 40 GB ATA/100 hard disk drive, TNT 2 M64 graphics card, Sony 52x CD-ROM drive, onboard soundcard							149	32.6	21.3	44	34.4	B
Pentium 4 1.4 GHz processor, 128 MB RDRAM, i850GB chipset based motherboard, 40 GB ATA/100 hard disk drive, Riva TNT2 M64 graphics card, Sony 52x CD-ROM drive, onboard soundcard							248	76.9	25.3	36	35.2	B
Pentium III 866 MHz processor, 64 MB SDRAM, 20 GB hard disk drive, Intel 810 chipset based motherboard onboard graphics card, Sony CD-ROM drive (speed?), onboard soundcard							215	26.5	18.8	54	27.4	B
Pentium III 852 MHz processor, 64 MB SDRAM, Intel 810 based motherboard, 20 GB hard disk drive, onboard graphics card, 52x CD-ROM drive, onboard soundcard, 56K modem							207	27.3	18.3	53	27.1	B
Coppermine 1 GHz processor, 64 MB PC133 SDRAM, i815 based motherboard, 20 GB Fujitsu MPG3204AT hard disk drive, inte- grated graphics card, 52x CD-ROM drive, IDE interface, onboard soundcard, 15-inch monitor							186.2	36.7	19.9	48	25.7	B
AMD Athlon 1.4 GHz processor, 128 MB DDR RAM, KT266 based motherboard, 40 GB ATA/100 hard disk drive, Riva TNT2 64 MB graphics card, 8x DVD drive, IDE interface, Creative Vibra 128 soundcard, Ace 56K modem, 17-inch monitor							104.93	77.1	25.3	24	41.2	B+
Pentium III 1 GHz processor, 64 MB SDRAM, i810 based motherboard, 20 GB ATA/66 hard disk drive, integrated graphics card, 48x CD-ROM drive, IDE interface, integrated soundcard, 56K modem, 15-inch monitor							224.22	26.7	17.8	48	23.2	B+
Pentium 4 1.5 GHz processor, 128 MB RDRAM, i850GB based motherboard, 40 GB ATA/100 hard disk drive, GeForce 3 64 MB DDR graphics card, 48x CD-ROM drive, 12x DVD drive, IDE interface, Turtle Beach Santacruz soundcard, 17-inch monitor							210.07	193.7	189	34	36.1	A-
Pentium 4 1.4 GHz, 128 MB RDRAM, ASUS P4T-M, 40 GB ATA/100, GeForce 2MX 400 32 MB graphics card, 16x DVD Pioneer drive, IDE interface, Yamaha soundcard, 56K internal modem, 15-inch monitor							219.36	47	23.3	35	32.4	B+
Pentium 4 1.4 GHz processor, 128 MB PC800 RDRAM, i850GB based motherboard, 20 GB ATA/66 hard disk drive, TNT2 M64 graphics card, Creative 12x DVD drive, IDE interface, onboard soundcard, 15-inch monitor							223.5	Failed	Failed	38	31.5	B