



	Creative Audigy Platinum	Creative Sound Blaster Live! Value	Creative Sound Blaster Extigy	Creative Sound Blaster Live! DE 5.1	Creative Vibra 128
Features					
General Specifications					
Chipset Used	Audigy	EMU10K1	Extigy	EMU10K1	ES1371
Speaker support	5.1	4.1	5.1	5.1	2
In-built Amplifier	✗	✗	✗	✗	✓ (only for Line Out)
API Support	DirectSound, DS3D, EAX 1.0, EAX Advanced HD, EAX 2.0, I3DL2 and A3D 1.0	DirectSound, DS3D, EAX 1.0, EAX Advanced HD, EAX 2.0	DirectSound, DS3D, EAX 1.0, EAX Advanced HD, EAX 2.0, I3DL2 and A3D 1.0	DirectSound, DS3D, EAX 1.0, EAX Advanced HD, EAX 2.0, I3DL2 and A3D 1.0	DirectSound, DS3D
Dolby Digital 5.1 decoding	✓	✗	✓	✓	✗
Operating System	Windows 3.x/95/98/NT/2K/XP, MS-DOS, Linux	Windows 3.x/9x/NT/2K/XP, MS-DOS	Windows 3.x/9x/NT/2K/XP, MS-DOS	Windows 3.x/9x/NT/2K/XP, MS-DOS	Windows 9x/NT/2K/XP, MS-DOS
MIDI Synthesizer					
Synthesis type (Wavetable / FM Synthesis)	Wavetable	Wavetable	Wavetable	Wavetable	Wavetable
Wavetable Memory	Based on System RAM (up to 1 GB)	Based on System RAM (up to 32 MB)	Based on System RAM (up to 1 GB)	Based on System RAM (up to 32 MB)	Based on System RAM
Sample Sets (MB)	4, 8	2, 4, 8	2, 4, 8	2, 4, 8	2, 4, 8
Polyphony (Hardware, Software voices)	64, 512	64, 512	64, 512	64, 512	128, NA
Midi Channels	48	48	48	48	16
SoundFont Support	✓ (including SoundFont 2.1)	✗	✓	✓	✗
Digital Audio Features					
Duplex Type	Full	Full	Full	Full	Full
Maximum Recording Depth & Rate	16 bit @ 48 KHz	16 bit @ 48 KHz	24 bit @ 96 KHz	16 bit @ 48 KHz	16 bit @ 48 KHz
Max. Playback Depth & Rate	24 bit @ 96 KHz	16 bit @ 48 KHz	24 bit @ 96 KHz	16 bit @ 48 KHz	16 bit @ 48 KHz
Signal-to-Noise Ratio (dB)	100	96	100	96	90
Connectors					
Microphone In	✓	✓	✓	✓	✓
Line In	✓	✓	✓	✓	✓
Line Out (Front channel)	✓	✓	✓	✓	✓
Line Out (Rear channel)	✓	✓	✓	✓	✗
Center / Sub Woofer Out	✓	✗	✓	✓	✗
S/PDIF Out (6 channel output)	✓	✗	✓	✗	✗
MIDI / Joystick Port	✓	✓	✓	✓	✓
CD In	✓	✓	✓	✓	✓
Telephone Answering Device (TAD) In	✓	✓	✓	✓	✓
Auxiliary In	✓	✗	✓	✗	✓
Help & Documentation					
Listing of specifications	✓	✗	✗	✗	✗
Quick setup guide	✓	✗	✗	✗	✗
Troubleshooting	✗	✗	✗	✗	✗
Contact information for after sales support	✗	✗	✗	✗	✗
Performance					
Sound Quality					
Sound Tracks (Scale of 5)	2.8	2.0	2.2	2.2	2.0
Quake III Arena Map DM9 (Scale of 5)	3.3	3.3	3.7	3.8	3.0
CPU Utilisation					
Quake III Arena Map DM9 at Normal / High Quality Sound (fps)	47.3 / 48.3	46.8 / 47.7	47.4 / 43.6	48.3 / 47.1	28.4 / 28.4
3D Audio Winbench (%)	1.59	Failed	6.81	5.11	5.33
Technical Test (RMAA 3.4)					
Frequency Response (dB)*	-1.66, +2.37	-0.58, +3.67	-0.92, +0.66	-4.81, +21.56	-0.66, +1.79
Signal-to-Noise level (dB)**	-80.8	-85.1	-104.3	-79.9	-60.7
Dynamic Range (dB)**	78.5	81.8	92.5	76.9	58.3
Total Harmonic Distortion + Noise (%)***	0.0042	0.0057	0.0047	0.0086	32.0379
Stereo Cross Talk (dB)**	-79.1	-83.0	-104.0	-85.7	-34.8
Warranty & Support					
Number of authorised service centres	18	18	18	18	18
Number of cities where service centres are present	18	18	18	18	18
Period of warranty (Years)	1	1	1	1	1
Overall Score					
Features (30%)	28.00	17.50	28.50	22.50	11.00
Performance (40%)	33.21	24.70	25.16	27.04	23.41
Warranty & Support (10%)	6.00	6.00	6.00	6.00	6.00
Value for Money (20%)	2.75	11.47	2.78	11.86	22.26
Overall Product Rating	69.96	59.67	62.44	67.40	62.67
Overall Grade	A-	B	B+	A-	B+
Vendor name	Compuage Infocom Ltd	Compuage Infocom Ltd	Compuage Infocom Ltd	Compuage Infocom Ltd	Compuage Infocom Ltd
E-mail	info@compuageindia.com	info@compuageindia.com	info@compuageindia.com	info@compuageindia.com	info@compuageindia.com
Price (In Rupees)	13,915	2,300	12,075	2,610	966

Disclaimer: * Lower the difference, the better

** Higher the better

*** Lower the better

† Integrated audio