

CATEGORY

MID RANGE DIGITAL CAMERAS

	Canon	Canon	Fuji	Fuji	Fuji	Fuji	
Model	Digital IXUS 400	PowerShot S50	FinePix S304	FinePix M603	FinePix F601	FinePix F410	
CAMERA FEATURES	Max. Image resolution	2272 x 1704	2592 x 1944	2048 x 1536	2832 x 2128	2832 x 2128	2304 x 1728
	CCD sensor (Megapixel)	4	5	3.2	3.1	3.1	3.1
	Focal length (35 mm equivalent)	36 to 108	35 to 105	38 to 228	38 to 76	36 to 108	39 mm
	Optical Zoom	3x	3x	6x	2x	3x	3x
	Digital Zoom	3.6x	4.1x	3.2x	4.4x	4.4x	4.4x
	Macro focus range (cm)	30 to 46	10 to 50	10 to 80	20 - 80	20 - 80	6 to 65
	ISO setting	50, 100, 200, 400	50, 100, 200, 400	equivalent to 100	160, 200, 400, 800, 1600	160, 200, 400, 800, 1600	200 ,400, 800, 1600
	White balance settings	Auto, 5 modes	Auto	Auto, 5 modes	Auto, 7 modes	Auto, 7 modes	Auto, 7 modes
	Shutter speed range	15 to 1/2000	15 to 1/1500	3 to 1/1500	1/4 to 1/2000	1/2 to 1/2000	1/2 to 1/2000
	Metering modes	Equivalent metering, Center-weighted, averaging/Spot metering	Equivalent metering, Center-weighted, averaging/Spot metering	64-zone TTL metering, Program AE	64-zone TTL metering	64-zone TTL metering	64-zone TTL metering, Program AE, exposure compensation in manual mode
Number of flash modes	Auto, Red-Eye Reduction, auto-on, auto-off, Slow Synchro	Auto, Red-Eye Reduction, auto-on, auto-off	Auto, Red-Eye Reduction, Forced, Suppressed, Slow Synchro, Red Eye+Slow Synchro	Auto, Red-Eye Reduction, On, Off, Slow Synchro	Auto, Forced, Suppressed, Slow Synchro	Auto, Red-Eye Reduction, Forced, Suppressed, Slow Synchro	
PHYSICAL FEATURES	Dimensions (l x w x d) cms	87 x 57 x 27.8	112 x 58 x 42	99.7 x77.3 x 69.3	64.5 x 93.3 x 31.6	72 x 93 x 34	77 x 69 x 22
	Weight (grams)	185	260	295	240	220	125
	Electronic viewfinder	✗	✗	✓	✗	✗	✗
	Compressed image format	JPEG	JPEG	JPEG	JPEG	JPEG	JPEG Exif ver 2.2
	Memory types supported	Compact Flash	Compact Flash	xD-Picture Card	xD-Picture Card, CF, MicroDrive	SmartMedia	xD-Picture Card
	Memory included (MB)	32	32	16	16	16	16
	Power Functions (scale of 5)	3	3	2	3	2	3
	Battery form factor	Li-Ion, Custom	Li-Ion, Custom	AA	Li-Ion, Custom	Li-Ion, Custom	Li-Ion, Custom
ERGONOMICS	Comfortable to hold (0-5)	3.5	3	4	2	2	2
	Rubber grip	✗	✗	✓	✓	✗	✗
	Menu navigation ease (0-5)	3	3.5	4	3.5	3.5	3.5
	Comfortably sized buttons (0-2)	1.5	1.5	1.5	1	1	0.5
	Special menu navigation buttons	NA	Four-way	NA	Four-way	Joystick	Two-way
	Build quality of flaps (memory, video/USB door)	Average	Average	Average	Average	Average	Average
PERFORMANCE	Image Test (Photoshop)						
	Red (mean)	133.08	145.97	148	141.53	151.08	127.23
	Green (mean)	99.43	86.03	97.28	90.81	96.21	69.07
	Blue (mean)	100.97	71.4	81.44	70.5	86.28	66.49
	Luminosity (mean)	109.68	102.32	110.67	103.69	111.51	86.17
	Specular Effect (scale of 5)	4	4	4.5	3.5	3	2
	Gradation in shading (scale of 5)	3.5	4	4.5	3	3.5	1
	Details Test (0-2 each)						
	Zone 1 Colour reproduction	1.5	1.5	1.5	1	1	1.5
	Zone 2 Text and wrinkles	1.5	1.5	1.5	1.5	0.5	1
	Zone 3 Details	1.5	1.5	1	1.5	1	1
	RGB Target Test						
	Red (mean)	154.11	164.51	184	120.81	173.49	174.44
	Green (mean)	120.18	70.41	66.97	43.75	74.84	72.34
	Blue (mean)	56.18	169.5	169.04	119.65	165.05	151.96
	Zoom Test						
	Quality (Scale of 5)	3.75	2.5	3.5	3	3.5	2.5
	Actual Person Image Test						
	Quality (Scale of 5)	3.5	4	3	2	3	2
W & S	Period of warranty (Years)	1	1	1	1	1	1
	Number of authorised service centres	NA	NA	1	1	1	1
	Number of cities where service centres are present	8	8	1	1	1	1
OVERALL SCORE	Camera Features (30%)	15	16	16	15	16	17
	Physical Features (15%)	7	5	3	5	4	7
	Performance (50%)	26.64	23.67	25.24	21.77	22.44	13.87
	Ergonomics (5%)	3.2	3.3	4	2.5	2.9	2.9
	Value for Money	8.16	6.4	10.76	7.62	7.64	9.32
	Grade	C+	C	B	C+	C+	B