



Motherboards									
Boards Above Rs. 10,000 and Up To Rs. 18,500									
Brand Model No.	MSI P45 Platinum	BioStar T-Power I45	ASUS M3A79-T Deluxe	ZOTAC NF-780i Supreme	ASUS P5Q3 Deluxe	EVGA 132-CK-NF78	MSI X48c Platinum	Intel DX48BT2	XFX MB-N780-ISH9
Chipset	Intel P45	Intel P45	AMD 790FX	NVIDIA nForce 780i	Intel X48	NVIDIA nForce 780i	Intel X48	Intel X48	NVIDIA nForce 780i
Socket	LGA 775	LGA 775	AM2/AM2+	LGA 775	LGA 775	LGA 775	LGA 775	LGA 775	LGA 775
Northbridge / Southbridge	P45 / ICH10R	P45 / ICH10R	AMD 790FX / AMD SB750	nForce 780i SLI / nForce 570 SLI	X48 / ICH9R	nForce 780i SLI / nForce 570 SLI	X48 / ICH9R	X48 / ICH9R	nForce 780i SLI / nForce 570 SLI
Price (Rupees)	10800	10800	11925	12999	13850	14250	15000	16000	16500
Plus (+)									
Minus (-)									
Grand Total (Out of 100)	69.41	64.51	65.91	67.89	76.15	67.62	68.55	68.03	66.14
Features (out of 60)	34.10	29.16	35.60	32.94	40.20	33.18	33.33	32.48	31.74
Performance (Out of 40)	35.32	35.35	30.31	34.95	35.95	34.44	35.22	35.56	34.40
Front Side Bus Speed (MHz)	1333 MHz	1333 MHz	2000 MHz	1333 MHz	1333 MHz	1333 MHz	1333 MHz	1333 MHz	1333 MHz
Memory Type	DDR2	DDR2	DDR2	DDR2	DDR2	DDR2	DDR2 / DDR3	DDR3	DDR2
Max Memory Supported (GB) / No of DIMMs	8 GB / 4	8 GB / 4	16 GB / 4	8 GB / 4	8 GB / 4	8 GB / 4	8 GB / 6 #	8 GB / 4	8 GB / 4
No. of SATA / IDE Ports	8 / 1	6 / 1	6/1	6 / 1	8 / 1	6 / 1	4 / 1	6 / 1	6 / 1
E-SATA Support / No of E-SATA Ports	✓ / 1	✓ / 2	✓ / 1	✗ / NA	✓ / 1	✗ / NA	✓ / 2	✓ / 2	✗ / NA
No of PCI Express Graphics Slots	2	2	4	3	3	3	2	3	3
No. of PCI / PCI x1 / PCI x4 Slots	2 / 2 / ✗	2 / 2 / ✗	2 / ✗ / ✗	2 / 1 / ✗	2 / 2 / ✗	2 / 1 / ✗	3 / 2 / ✗	2 / ✗ / ✗	2 / 1 / ✗
Multi GPU Support (SLI/CrossFire/N) / No of PCIe Lanes for multi-GPU setups	Y / Crossfire x8	Y / Crossfire x8	Y / Quad CrossfireX (x8, x8, x8, x8)	Y / 3 way SLI (x16, x16, x8)	Y / Crossfire x8	Y / 3 way SLI, (x16, x16, x8)	Y / Crossfire x16	Y / Crossfire x16	Y / 3 way SLI, (x16, x16, x8)
Integrated Audio Controller	Realtek ALC 888	Realtek ALC 888	ADI AD2000B SoundMax	Realtek ALC 888	ADI 1988B	Realtek ALC 888	Realtek ALC 888	Sigmatel STAC 927	Realtek ALC 888
SPDIF / Optical Port	✗ / ✓	✗ / ✗	✓ / ✓	✗ / ✓	✓ / ✓	✗ / ✓	✗ / ✓	✗ / ✓	✗ / ✓
No of LAN Ports / 10/100 / Gigabit	1 / Gigabit	1 / Gigabit	1 / Gigabit	2 / Gigabit	2 / Gigabit	2 / Gigabit	1 / Gigabit	1 / Gigabit	2 / Gigabit
Integrated Wi-Fi (Y/N)	✗	✗	✗	✓ (kit)	✓	✗	✗	✗	✗
No. of rear USB / FireWire Ports	6 / 1	6 / 0	6 / 1	6 / 1		6 / 1	6 / 1	8 / 1	6 / 1
All Solid State Caps (Y/N)	✓	✓	✓	✗	✓	✗	✓	✗	✗
BIOS options									
Overclocking / Overvolting (So 10)	7.25 / 7	5 / 5	7.25 / 7	7 / 7	9 / 9	7 / 7	7.25 / 7.25	7.75 / 7.5	7 / 7
CPU voltage range (volts)	0.9925 to 1.9425 V	-0.05v to +1.3v	0.8 to 1.7v	0.5 to 1.8.0v	0.85 to 2.1v	0.5 to 1.8.0v	+0.7875 V at 0.0125	1.28 to 1.6v	0.5 to 1.8.0v
Memory voltage range (volts)	1.428 to 3.324 V	+0.4v to +1.85v	1.8 to 2.5v	1.8 to 2.5v	1.5 to 2.78v	1.8 to 2.5v	DDR3 - 1.50 to 2.75 V, DDR2 - 1.8 to 3.3 V	1.5 to 2.5v	1.8 to 2.5v
Package Bundle									
No of SATA / PATA Cables Provided	4 / 1	4 / 1	6 / 1	4 / 1	6 / 1	6 / 1	4 / 1	2 / 1	4 / 1
CD's	Drivers	Drivers	Drivers	Drivers	Drivers	Drivers	Drivers	Drivers	Drivers
Other Miscellaneous Accessories	USB and FireWire bracket	Add-on fan with heatpipe	NA	WiFi kit	2-WiFi AP units	NA	USB and FireWire bracket	NA	NA
Performance									
PC Mark 2005:									
CPU / Memory	9662 / 6552	9678 / 6471	7658 / 4500	9612 / 6682	9700 / 6738	9644 / 6706	9652 / 6452	9672 / 6482	9635 / 6735
Graphics / HDD	18382 / 6827	18499 / 7073	16798 / 6881	18284 / 7243	18435 / 6958	18371 / 7241	18182 / 7026	18236 / 7172	18373 / 7102
Overall	10389	10499	8969	10473	10624	10512	10445	10219	10480
SiSoft Sandra 2008:									
CPU Arithmetic (Dhrystone ALU / Whetstone iSSE3)	55328 / 44217	55631 / 44045	39486 / 33576	55538 / 44263	55683 / 44307	55555 / 44015	55262 / 44192	55527 / 44091	55533 / 44024
CPU Multimedia (Integer / Floating)	329873 / 180626	330244 / 181007	98962 / 130438	329374 / 180731	330655 / 181060	329422 / 180295	329872 / 180828	330283 / 180992	329374 / 180353
Drive Index (MB/s) / Random Access Time (ms)	73 / 6	72 / 6	72 / 6	67 / 13	72 / 6	67 / 13	72 / 6	74 / 6	67 / 13
SiSoft Memory bandwidth score (Integer / Floating)	6626 / 6656	6658 / 6668	5312 / 5311	6838 / 6841	7324 / 7222	6972 / 6957	7019 / 7023	7219 / 7215	6839 / 6837
3D Mark 2006 Marks / CPU Score	16563 / 4982	16845 / 4966	13715 / 3907	16377 / 4981	16928 / 4991	16707 / 4954	16627 / 4945	16823 / 4993	16703 / 4938
CINEBENCH R10 (CPU)	11825	11833	8408	11836	11831	11821	11836	11862	11834
WinRAR 3.8	2204	2086	1850	2253	2289	1603	2122	2219	1672
Video Encoding (DivX 6.8) Time (sec)	114.6	114.1	78.3	113.5	113.2	113.8	114.8	113.9	113.4
File Transfer Test (4 GB File) (MBps)	136.6	137	140.4	146.7	137	143.7	140	137.6	145.8
Doom 3 FPS (1600x1200, 4xAA, 4xAF / 640 x 480, low detail)	201.6 / 296.3	208.7 / 291.7	177.1 / 190.8	208.4 / 303.7	212.7 / 302.2	211.8 / 303.8	207.5 / 292.4	208.2 / 294.3	208.35 / 299.4
S.T.A.L.K.E.R Shadow Of Chernobyl (1680x1050, 4xAA, 4xAF / 800 x 600, low detail)	180.63 / 908.72	180.32 / 916.3	139.29 / 460.81	180.21 / 905.3	181.11 / 930.72	179.01 / 880.41	180.4 / 911.4	179.3 / 910.3	179.5 / 901.4
Prey (1680 x 1050, 4x AA, 4x AF, 640 x 480, low detail)	206.3 / 351.7	210.5 / 352.6	183.6 / 231.9	206.3 / 346.4	211.1 / 374	208.7 / 344.9	208.8 / 350.3	208.6 / 355	208.5 / 348.3