



Scoreboard

15-inch LCD Monitors

BRAND	Acer	Aopen	BenQ	CMV	Digi-View	HCL	LG	NEC
Model	AL1512	F1513	FP537s	CT-529A	DGL-115AS	HCM 510LSA	Flatron L1530S	AccuSync LCD 52V
Features								
Pixel Pitch	0.297	0.297	0.297	0.297	0.297	0.297	0.297	0.279
Luminance (cd/m2)	350	250	250	450	250	250	250	250
Contrast Ratio	450:1	400:1	400:1	500:1	350:1	500:1	400:1	400:1
Native Resolution	1024x768	1024x768	1024x768	1024x768	1024x768	1024x768	1024x768	1024x768
Response time (ms)	23	25	15	16	25	16	16	25
W x H x D (cm)	34.6x33.7x18	35.5x36.5x19	33.8x33.1x13.6	34.8x34.4x18.6	47x45x14	35.6x35.5x15	36.8x39.9x21	34.4x35.2 x16.5
Weight (KG)	2.5	2.9	3.7	2.6	3.3	3	3.6	3.2
USB hub (Y/N) / No. of ports	✗	✗	✗	✗	✗	✗	✗	✗
Built in Speakers (Y/N)/watts	✓/NA	✓/2W	✗	✓/NA	✓/NA	✓/1W	✗	✗
VESA Wall Mount	✓	✓	✓	✓	✓	✓	✓	✓
Swivel Base (Angle) verticle/horizontal axis	✗/✓	✓/✗	✓/✗	✗/✓	✓/✓	✗/✓	✗/✓	✗/✓
Height Adjustment (cm)	✗	✗	✗	✗	✗	✗	✓	✗
Landscape/Portrait	✗	✗	✗	✗	✗	✗	✗	✗
In-built TV Tuner	✗	✗	✗	✗	✗	✗	✗	✗
Power Consumption (W)	33	30	30	33	25	35	25	21
Input types	D-Sub, Stereo pin	D-Sub, Stereo pin	D-Sub	D-Sub, Stereo pin	D-Sub, Stereo pin	D-Sub, Stereo pin	D-Sub, Stereo pin	D-Sub
Bundled Accessories (Manuals, Colour Profile, Driver and Calibrating software...)	Quick setup guide, Electronic user's guide on CD	Power/D-sub cable and power adapter	Quick start guide, Driver and Manual on CD	Quick setup guide, Electronic user's guide on CD	User guide, Driver CD, Calibrating software	Quick setup guide, Electronic user's guide on CD	User guide, Driver CD, Calibrating software	NaViSet software,
DISPLAYMATE VIDEO EDITION								
Sharpness and resolution								
Point shape and visibility	3	2.25	3	2.75	3.5	2.75	2.625	3.5
Video Bandwidth test	3.25	2.5	3.625	3.75	3.875	3.375	3.875	3.5
Colour and Gray-Scale								
Streaking and Ghosting	5	3	5	5	5	5	5	5
Bar Streaking	5	3.25	4.5	5	4.875	3.5	5	5
Colour Streaking	5	2.75	4.875	4	4.875	4	4.875	4.75
Mid-Range streaking	3.25	2.75	3.25	2.75	3.5	2.5	3.5	3
White-level shift	3.875	2	3.375	3	3.25	3.25	3.375	3.75
Black-Level shift	3.5	3	3.25	3.25	3.5	3.25	3.375	3.5
RGB purity	4	4	4	4	4	4	4	4
Text colour combination	3.375	3	3.625	2.25	2.75	2.375	3.25	3.5
16 intensities levels	3.375	3.75	4.5	4.25	4.25	4.25	3.875	3.75
64 intensities for primary colours	3.125	3.125	3.75	3.75	3	3.375	2.875	3.25
64 intensities for secondary colours	3.25	3.25	4	4	3.25	3.375	2.875	3.25
256 intensities level	3.25	3.25	4	3.875	3.375	3.125	3	3.25
Colour scales	3.25	3.25	4.25	4.125	3	3.125	3.125	2.75
Miscellaneous tests								
Reverse Video Contrast	3.75	3.75	3.75	3.25	4	3.75	4	3.75
Screen uniformity	3.5	3	4.375	3.125	3.25	3.375	3.25	3
Passmark Monitor Test								
Pixel Persistence test (So5)	1	0.5	0.5	0.75	0.75	0.5	0.375	0.5
Miscellaneous tests								
Movie Test (ghosting effect)	2.375	2.5	1.25	2.875	2.625	2.5	2.25	2
Viewable angle test (Text)	147.5	152.5	155	150	140	137.5	150	155
Viewable angle test (Movie)	135	137.5	125	125	122.5	122.5	135	125
OSD usability test	4	2.5	4	4	4	4	4	3.5
OVERALL SCORE	70.20	55.19	63.32	66.07	65.18	61.41	58.07	55.92
Feature	7.25	6.15	6.23	7.21	7.00	6.00	5.84	4.40
Performance	44.95	37.79	46.17	43.86	44.33	41.55	43.66	43.52
Price Index	18.00	11.25	10.92	15.00	13.85	13.86	8.57	8.00
Price (Rs)	9,999	16,000	16,490	12,000	13,000	12,990	21,000	22,500

Sharpness and Resolution

We checked for the sharpness of the image using the Point Shape and Visibility screen in Display-Mate, consisting of a fine white dot. We looked for pixel bleeding, and found that most monitors had some amount of bleeding at

the edge. This bleeding results in a red, green or blue tinge at the edge of the dot. Only the ViewSonic VE510b (15-inch) and VA712 (17-inch) returned acceptable results.

In the video bandwidth test, a fine white line is drawn on a black background. This screen is

used to see how accurately the lines are drawn and whether there are any discrepancies.

In the 15-inch category, the AOpen and S-Media displayed blue tinges running across the length of the line at the edge, whereas the Winsonic L1562S, due to its high brightness,