

Scoreboard Intel Motherboards									
BRAND	AOpen	ASRock	ASUS	Foxconn	Foxconn	Gigabyte	Gigabyte	Gigabyte	Gigabyte
Model	i915Gm-I	775Dual-915GL	P5P800-MX	865M01-G-6LS	915PL7AE-8S	GA-8I915ME	GA-8IG1000-G	GA-8I915GV-MF	GA-8TR5 350MT
Chipset	Intel 915G	Intel 915G	Intel 865GV	Intel 865G	Intel 915PL	Intel 915	Intel 865G	Intel 915GV	ATI RS350
Interface type	LGA 775	LGA 775	LGA 775	Socket 478	LGA 775	LGA 775	Socket 478	LGA 775	Socket 478
Features	27.1	22.1	20.42	22.94	25.86	19.46	27.72	22.76	25.82
Memory Speed Supported/Max memory	400/4GB	400/2GB	400/4GB	400/2GB	400/2GB	DDR400/2GB	400/4GB	400/4GB	400/4GB
Form Factor	Micro ATX	Micro ATX	Micro ATX	Micro ATX	Micro ATX	Micro ATX	Micro ATX	Micro ATX	Micro ATX
Onboard/Graphics Port/Type	Y/x16/PCIE	Y/8x/AGP	Y/8x/AGP	Y/8x/AGP	PCI-E x16/AGP 8x	Y/x16/PCIE	Y/8x/AGP	Y/x16/PCIE	Y/8x /AGP
PCI Slots	2	2	3	3	3	2	5	2	3
Onboard Sound (Channels)	7	8	6	6	8	6	8	8	6
Onboard FireWire/Firewire b	0	0	0	0	0	0	0	0	0
USB									
USB 1.1 (Nos)/USB 2.0 (Nos)	4	4	4	4	4	4	2	4	4
Ethernet/Gigabit Ethernet	10/100	10/100	10/100	10/100	Gigabit	10/100	Gigabit	Gigabit	10/100
RAID 0, 1, 0+1	✗	✗	✗	✗	0,1,0+1	✗	✗	✗	0,1
SATA	4	4	4	2	4	2	2	4	2
SATA RAID	✗	✗	✗	✗	✓	✗	✗	✗	✓
HyperThreading Support	✓	✓	✓	✓	✓	✓	✓	✓	✓
Power Supply Type (Pins)	24	20	24	20	24	24	20	24	20
Component layout (S05)									
Capacitors near the CPU socket	4	4	3.5	3.5	4	4	3	4	3.5
Placement of IDE and SATA connectors	4	4	3	3.5	2.5	3	3	4	3.5
Memory Slots and the lock on the AGP slot	4	2.5	3	3	3	2.5	3.5	3	3
AGP slot with locks	5	0	0	5	5	5	5	0	5
Locking mechanism of the processor	4	4	4	3.5	4	4	3.5	4	3.5
Interference of AGP card with PCI card	4	3	3	3	4	3	3	0	3
Colour coding of Memory slots and front USB	2.5	0	2.5	0	0	0	2.5	2.5	2.5
Package contents									
Manual	✓	✓	✗	✓	✓	✗	✓	✓	✓
CD's	✓	✓	✓	✓	✓	✓	✓	✓	✓
Necessary cables	✓	✓	✗	✓	✓	✗	✓	✓	✓
Other Miscellaneous Features									
Performance	22.77	22.61	24.73	22.14	31.05	23.71	22.29	23.52	23.79
Serious Sam Second Encounter									
Normal (640x480x32)	43.5	44.2	54.3	50.9	152.4	45.9	42.1	45.7	54.6
High (800x600x32)	39.6	40.1	47.4	37.8	133.1	41.8	34.9	41.4	47.5
Quake3 Arena									
Normal (640x480x32)	133.5	135.5	151.4	84.1	370.7	148.2	99	140.2	178.5
High (800x600x32)	130.7	132.4	125.1	57.4	282.1	142.6	78.4	135.8	131.7
3D Mark 2001 SE	5106	5115	5762	2812	9101	5516	3096	5301	5414
PC Mark 2004									
CPU Index	4284	4311	4815	4839	5481	4644	4763	4589	4429
Memory Index	4658	4316	5176	4369	5154	4807	4384	4756	4080
Graphics	1026	1028	1054	581	1669	1043	657	1039	1520
Disk Index	4876	4877	4793	4909	4866	4222	4195	4919	4835
Total Score	3660	3452	4508	3820	4945	3907	4043	3928	4344
Sisoft Sandra 2005 Professional									
Memory sub-system									
ALU/RAM	4670	4050	4564	4303	4524	4541	4213	4641	4008
FPU/RAM	4659	4055	4550	4315	4537	4543	4212	4638	4002
CPU sub-system									
CPU Dryhstone	8139	10412	10417	9850	10454	8715	9811	8718	9779
CPU Whetstone	3342	3361	4309	4014	4297	3591	4018	3571	4023
Multimedia - CPU Integer	19750	19910	24255	24584	25476	21166	24733	21183	24753
Multimedia - FPU SSE	26125	26321	28676	35115	33835	27971	34645	28198	34370
Disk drive									
Drive Index MB/sec	46	46	47	47	47	51	51	46	46
Sequential Read MB/sec	57	57	57	57	57	57	57	57	56
Random Read MB/sec	26	26	30	30	27	41	41	27	27
Sequential Write MB/sec	56	56	56	57	56	57	57	56	56
Random Write MB/sec	43	45	47	46	46	46	45	47	47
Average access time	20	20	15	19	20	7	7	20	18
Zdbench Business Winstone 2004	21.1	21.8	25	22.6	26.1	21.1	21.9	21.6	22.6
Video Encoding (Time in secs)	150	146	152	142	120	142	138	145	142
Price Index	8.00	9.25	8.41	10.20	8.86	9.74	9.05	7.60	9.50
Price (Rs)	4750	4110	4520	3725	4290	3900	4200	5000	4000
	57.87	53.95	53.55	55.28	65.77	52.91	59.05	53.88	59.11