





Scoreboard

High-end Intel Motherboards


BRAND	ASUS	ASUS	ASUS	ECS	Foxconn
Model	Proactive P5AD2-E Premium (W.E.)	P5LD2-VM-UAYZ	Proactive P5ND2-SLI Deluxe	PF21 Extreme	955X7AA
Chipset	Intel 925XE	Intel 945G	NVIDIA nForce4 SLI	Intel 925 XE	Intel 955X
Features	29.34	21.11	35.60	25.34	28.62
Maximum CPU supported	P-4	P-4 Dual Core	P-4 Dual Core	P-4	P-4 Dual Core
Memory Type/Speed	DDR II/711/4	DDR II/667/4	DDR II/667/4	DDR II/533/4	DDR II/667/4
Supported(MHz)Max memory					
SLI	6	6	4	6	6
PCI Slots	3+2 PCIe	2+1 PCIe	3+2 PCI	3 + 3 PCIe	3 + 3 PCIe
Onboard FireWire/Firewire b	Pin header 2/b	6	1/a	1/a	1/b
BlueTooth/WiFi	6/4	6/6	6/6	6/6	6/6
USB 1.1 (Nos)/USB 2.0 (Nos)	4	4	4	4	4
Ethernet Type (10/100/Gigabit)	Dual Gigabit	Gigabit	Dual Gigabit	Gigabit + 10/100	Dual Gigabit
RAID type	0,1,0+1,5,10,Matrix,JBOD	6	0,1,0+1,JBOD	0,1,0+1	0,1,0+1,5,Matrix
SATA Type/Number/Hot PnP	I/8/6	I/4/6	II/8/4	I/6/6	II/8/6
Miscellaneous	Coaxial and SPDIF out, WiFi antenna port	Intel GMA 900	External SATA port, SPDIF out	SPDIF IN/Out	Coaxial out
Component layout (SO5)					
Capacitors near the CPU socket	4.5	4	4.5	3.5	4
Placement of IDE and SATA connectors	4	4	3.75	4	3.5
Graphics slot with locks	5	5	5	5	5
Interference of AGP card with PCI slot	3	3	5	3	3
Package contents					
Manual/CDs	4/4	4/4	4/4	4/4	4/4
Necessary cables	10 SATA, 3 SATA power, IDE, floppy	2 SATA, SATA power, IDE, floppy	4 SATA, 2 SATA power, IDE, floppy	6 SATA, SATA power, IDE, floppy	2 SATA, 2 SATA power, IDE, floppy
Other Miscellaneous Features	D-bracket for communication port, D-bracket for 2 USB, D-bracket for 2 FireWire and LAN, External SATA connector,WiFi antenna	None	D-bracket for 2 USB and Game Port, D-bracket for FireWire, SLI bridge with retention bracket	D-bracket for 2 USB and FireWire, D-bracket for printer port, Top Hat BIOS recovery tool, cross over cable	D-bracket for 2 USB
Performance					
Far Cry 1024x868/1600x1200 (fps)	121.52/104.73	120.62/104.95	121.82/103.56	123.2/104.12	123.79/106.68
Doom 3 1024x868/1600x1200 (fps)	100.7/85.2	99.8/85	99.1/86.5	104.1/85.6	102.8/86.6
3D Mark 2005 Marks/CPU Marks	6959/4829	6932/4898	6957/4860	6943/5149	6967/5338
PC Mark 2004					
CPU Index/Memory Index	5245/5455	5393/5214	5283/5538	5518/5469	5486/5477
Graphics Index/Disk Index	8162/4333	8171/4342	8187/4672	8209/4427	8193/4406
Total Score	5415	5405	5410	5485	5464
SiSoft Sandra 2005 Professional					
ALU to RAM/FPU to RAM (MB/s)	4804/4799	4717/4718	4820/4809	4773/4774	4837/4838
CPU Dryhstone/Whetstone	10526/4302	10489/4279	10451/4307	10452/4273	10469/4287
Multimedia—CPU Integer/FPU SSE	25576/32722	25472/33989	25446/31750	25409/33793	25448/33902
Drive Index (MB/sec)/Average access time (sec)	50/8	49/8	50/8	46/8	44/8
Sequential/Random Read (MB/sec)	56/39	56/39	56/40	53/37	51/35
Sequential/Random Write (MB/sec)	56/43	55/42	56/41	52/37	52/38
ZDBench Business Winstone 2004	25.6	25.6	26.6	24.4	24.6
Video Encoding (sec)	119	121	120	118	119
Price Index	3.83	8.50	3.83	6.99	6.49
Price (Rs)	16,000	7,200	16,000	8,750	9,425
Total Score (Out of 100)	70.25	66.55	76.78	69.24	72.09



+ Good performance, WiFi capable
- Very Expensive, does not support dual-core CPUs




+ Good price to performance ratio
- Low on features and package contents



+ Good performance and SLI capable
- Very Expensive



+ Good price to performance ratio
- Does not support dual core processors



+ Good performance
- Ordinary package contents