



Microsoft Mobile Oy

Microsoft's acquisition of Nokia is complete and it has been rebranded
<http://dgit.in/MicroOy>



Google+ chief quits

Vic Gundotra is to leaving Google casting a shadow over the future of Google+
<http://dgit.in/ByeVic>

Digit Squad

The Engine

Go to www.pandajs.net and download the latest engine. After extracting the zip, you will find two folders *src* (engine and game main file) and *media* (assets – images, audio etc.). Inside the *src* folder you will find two files – *config.js* (path configurations) and *main.js* (your game code). You can find the source codes inside the engine folder or make your own and add it there.

Setting up the scene

Open *main.js* using a text editor. You would see the following:

```

game.module('game.main')
.body(function() {
  game.addAsset('logo.png');
  SceneGame = game.Scene.extend({
    backgroundColor: 0xb9bec7,
    init: function() {
      var logo = new game.Sprite('logo.png');
      logo.anchor.set(0.5, 0.5);
      logo.position.set(game.system.width / 2, game.system.height
/ 2);
      this.stage.addChild(logo);
    }
  });
  game.start();
});

```

- **game.module** – Configures which all modules the game needs.
- **game.addAsset()** – Assets (images, audio etc.) should be added before its referenced inside a scene. The above line adds the image *logo.png* from the media folder (path configured in *config.js*) to its assets set.
- To create a scene, we create a class which extends the *game.Scene* class. Several methods and properties are available for the *game.Scene* class. The *backgroundColor* property lets you paint the background a solid color.
- **init()** – is called to initialize the scene. Here we create a sprite of the PandaJs logo which we added to our assets set earlier.
- **anchor.set(x,y)** – Sets the registration point of the sprite. You can find a demo of what's an anchor point here <http://jawsjs.com/jawsjs/examples/example5.html>
- **position.set(x,y)** – Sets the x and y coordinates to display the sprite.
- **stage.addChild()** – Adds the sprite to the scene.
- **game.start()** – To start the game. You can specify which scene to start first, the dimension of the scene and the *CanvasId*. The parameters are in the order – *game.start(Scene,width,height,loaderClass,CanvasId)*.

Making the sprite interactive

To make the sprite interactive, we must include the *core.js* and set the sprite's interactive property to true. Below the *game.module* add the following –

```

.require("
  engine.core")

```

And inside the *init()* function, after creating the sprite class add -

```

logo.interactive = true;

```

Interactions are possible through keyboard and mouse. For mouse several methods like *click*, *mouseup*, *mousedown*, *mousemove* are supported. To make it do some function on click, we implement the *click* method as follows –

```

logo.click = function () { //your code to do something

```

Removing the sprite

To remove a sprite from the screen, call the *removeChild()* method from the scene or just *remove()* from the object itself. Like –

```

logo.click = function () {this.remove();}

```

Or

```

this.stage.removeChild(logo);

```

More?

That is pretty much the basics. You can find more about PandaJs on its official website. If you want to know more about HTML5 Game engines, head onto <http://html5gameengine.com/> and find which is right for you. There are plenty of frameworks to choose from and most of them are as easy as this one to work with. Happy coding! 🚀



PC, Laptop, Mobile, Tablet

Total सुरक्षा

Call: 9272707050
9822882566

india

antivirus

