



Another related concept is that of watchpoints. With watchpoints you can have the execution of a program halt when a particular variable or memory location is modified, without worrying about what the exact value is. The way to set a watchpoint is to use watch keyword followed by the name of the variable to watch. For examples: watch ctr to pause when the variable ctr is modified.

Once the execution of an application has paused, you might want to take it slow and go through your code one line at a time. There are number of commands for exactly this purpose, but the two most important ones are `step` and `next`, they are very similar in functionality but the difference between them is important.

Where step and next differ is in now they handle function calls in your code. If you have you main function call another function in your code (like we have our main function calling sumarr) then the next will treat this like a single instruction and continue on to the next line after the function call. On the other hand, step will move the execution of the code inside the called function and let you execute that line by line as well.

*pointers



>>Github has much more to it than what meets the eyes and this course teaches you how to use GitHub effectively.



>> This online course offered by MIT teaches you how videogames are built but also what cultural, social and educational significance they carry.

>> Learn how to program your own AI powered car directly by Google and Stanford's autonomous driving team's researchers.



>>Want to learn how to use the Office 365 APIs that let you access the cloud from a variety of platforms. Follow the link to find the course that does exactly that.. <http://doit.in/office365api>



If you're inside a function, and want to quickly get to the end of the function and see the return value, you can use the `finish` command.

While breakpoints halt the execution of code, you can use the `continue` command to resume executing the program till it reaches the next breakpoint (or the end of the program). If you want to continue executing the code till a particular line number use `until <line number>`.

The final thing you need to know (at least for the purposes of this basic introduction) is how to actually peek into the running program and display the values of various variables.

It can also print character strings automatically, however for other types of arrays, you need to be a little more specific. For instance if you wish to display an array called `arr` of length 10, you can use the `print` command as one of the following:

The third one above will try to automatically calculate the length.

