

cessor causing the reboot of the Linux system. This will lead to loss of data in the RAM of the Linux system.

Arduino™ Tre (Yet to be released, but incredibly powerful)

The Arduino™ Tre is the first high performance board that will be developed by the creators of Arduino™ in collaboration with BeagleBoard.org foundation. While it isn't released yet, developer edition boards are available to the developers for Beta testing. Not much detail is currently available about the Tre. More information about it will only be released after the final release.

The Arduino™ Tre integrates the power of a Sitara processor based Linux and the AVR-based Arduino™, while maintaining the simplicity of the Arduino™ software environment. Compared to the Arduino™ Leonardo or Uno, the 1-GHz Sitara AM335x processor on the Tre allows Arduino™ developers to get up to 100 times more performance. The ecosystem on the



Arduino™ Tre Board

Arduino™ Tre can run high-performance desktop applications, processing-intensive algorithms and high-speed communications opening doors to advanced applications that combine the power of the computing world and the hardware ecosystem with the simplicity of the Arduino™ environment.

The adoption of original Arduino™ hardware design allows use of various shields on the Arduino™ Tre. The developers expect the Tre to be used for building high performance applications such as:

- ◆ 3D printers
- ◆ Building automation and lighting automation
- ◆ Telemetry hubs to collect data from sensors
- ◆ Applications that need very fast control within given time limits

Hardware specs

Apart from the specifications of the on-board Atmel ATmega 32u4, the following additions have been made open:

As given in the list of specs, the Tre has pins with 3.3 V logic voltage level, making it necessary to convert the 5 V logic voltage to 3 V as needed in most applications.