

program to show you how to define the fibonacci function would be as follows:

- `fibonacci(0) -> 0 ;`
- `fibonacci(1) -> 1 ;`
- `fibonacci(N) when N > 0 -> fibo(N-1) + fibo(N-2) .`
- An example of immutable variables can be shown by trying to assign different values to a variable at different points in time: -
- `1> A = 456.`
- `2> A = 345.`
- `** exception error: no match of right hand side value 345`

Lists in Erlang are ever present and can be used for many operations. They can be defined by square brackets and can contain anything, even functions: -

- `3> [a,b,c,34,45,[1,2,3]].`
- `[a,b,c,34,45,[1,2,3]].`

Tuples are another data type which can be used for comparison operations and are defined with curly braces: -

- `4> {a,b,c,34,45,{1,2,3}}.`
- `{a,b,c,34,45,{1,2,3}}.`

Atoms are static string literals which are used internally for message passing and other such functions: -

- `5> hello.`
- `Hello`

This concludes our discussion and overview for this language but you can go through the links and documentation in the references section.

References

- ♦ <http://www.erlang.org/course/course.html>
- ♦ <http://www.erlang-in-anger.com/>
- ♦ <http://erlangcentral.org/>
- ♦ <https://www.erlang-solutions.com/>
- ♦ Joe Armstrong's Thesis: http://www.erlang.org/download/armstrong_thesis_2003.pdf
- ♦ Erlang Handbook: <http://opensource.erlang-solutions.com/erlang-handbook/>
- ♦ <http://chimera.labs.oreilly.com/books/1234000000726/index.html>
- ♦ http://en.wikibooks.org/wiki/Erlang_Programming 