

year whereas it costed around 1,540 Euro per year for storage of the same data volume in Hadoop.

Hadoop Environment Setup on Linux

Hadoop is supported by GNU/Linux. Therefore, we have to install a Linux operating system for setting up Hadoop environment. If you are using a different OS, you always have the option to install Virtualbox.

Step 1 : Create a separate user for Hadoop

Fire up the Linux Terminal and type in the following code :

- `$ su`
- `password: <Your Root Password>`
- `# useradd <username>`
- `# passwd <password>`
- `New passwd: <Your Password for New User>`
- `Retype new passwd: <Your Password for New User>`

Step 2 : SSH Setup and Key Generation

Before installing Hadoop into the Linux environment, we need to set up Linux using SSH (Secure Shell). SSH setup is required to do perform operations on a cluster. To authenticate users of Hadoop, it is mandatory to provide public/private key pair for a Hadoop user and share it with different users.

- `$ ssh-keygen -t rsa`
- `$ cat ~/.ssh/id_rsa.pub >> ~/.ssh/authorized_keys`
- `$ chmod 0600 ~/.ssh/authorized_keys`

Step 3 : Configure Java

Java is the main prerequisite for Hadoop. Please make sure that you have Java installed on your system and is made available to all the users. You can verify the existence of java in your system using the following command:

- `$ java -version`

Step 4 : Download Hadoop

To download Hadoop in your system, type in the following command in the terminal :

- `$ su`
- `password:`
- `# cd /usr/local`