

You would have noticed that inside the **doInBackground** method you have called for the **getFeeds** method. This is the method where you will be pulling all the RSS Feed data from the network. So, it's high time you got into doing some network operations. Firstly, you will instantiate the global variables headlines and links as **ArrayLists**, which you declared earlier. Next, you will define the URL source from which you are going to pull the RSS Feeds. Here, we are using Digit's RSS Feeds. You may feel free to try with any other source. Now, you shall fetch the XML content from an **Input Stream**. We will be defining a method **getInputStream** to do so, later in the chapter.

Once we have the XML content, we shall parse the XML content. We will be looking for the "<title>" tag that appears inside the "<item>" tag. However, we must also take in consideration that the name of the RSS Feed is also enclosed in a "<title>" tag.

Each and Every RSS Feed begins in the following format -

```
<channel>
<title>Feed_Name</title>
....
"
```

We will have to skip the "<title>" tag which falls under the "<channel>" tag, and only consider those "<title>" tags which falls under "<item>". To achieve our requirement we make use of a Boolean variable **insideItem**. We shall now fetch the starting tags and the ending tags and later based on the status of the previously declared boolean variable, fetch the headlines and the links. These headlines and links are stored in the global variables headlines and links. This process is continuously repeated till the end of the document is reached.

```
public void getFeeds()
{
    headlines = new ArrayList();
    links = new ArrayList();

    try {
        URL url = new URL("http://feeds.feed-
burner.com/digit/latest-from-digit");
        XmlPullParserFactory factory = XmlPullParserFactory.newInstance();
        factory.setNamespaceAware(false);
        XmlPullParser xpp = factory.newPullParser();
        xpp.setInput(getInputStream(url, "UTF_8"));
```