

```

• var postTitle: String = String()
• var postLink: String = String()
• var eName: String = String()

```

Then move on to initialising the `didStartElement` function whenever we come across the `elementName` as 'item'. This allows the app to see the individual item elements in the XML feed.

```

• func parser(parser: NSXMLParser!, didStartElement ele-
  mentName: String!, namespaceURI: String!, qualifiedName
  qName: String!, attributes attributeDict: [NSObject :
  AnyObject]!) {
•   eName = elementName
•   if elementName == "item" {
•       postTitle = String()
•       postLink = String()
•   }
• }

```

Now we are going to sanitise the text that we get from the elements. This helps make it look better and legible. Once sanitised we will store the elements into the individual variables we had declared earlier. Paste this code in the `foundCharacters` function.

```

• func parser(parser: NSXMLParser!, foundCharacters string:
  String!) {
•   let data = string.stringByTrimmingCharactersInSet(NSChara-
  cterSet.whitespaceAndNewlineCharacterSet())
•   if (!data.isEmpty) {
•       if eName == "title" {
•           postTitle += data
•       } else if eName == "link" {
•           postLink += data
•       }
•   }
• }

```

By using the `stringByTrimmingCharacterInSet` method we are performing the sanitisation by essentially removing all whitespaces and newline characters. Then we move through the item will we find the 'title' and 'link' elements and store them in `postTitle` and `postLink` variables, respectively. And once this is done we need to create an instance of the `ShowArt` which will then be added to the array to be displayed in the main view as the `showArts` array.