

Turn off IPv6

The Internet Protocol version 6(IPv6) brings in a new internet layer of the TCP/IP protocol suite which not only replaces IPv4 but also provides multiple benefits. There exist no decent tools at present with which you can check a system over network for seeking out IPv6 security issues. IPv6 protocol is set as default by most Linux distros. And bad traffic can be sent by crackers via IPv6 since most admins don't monitor it. Unless it's required for the network configuration, either disable IPv6 or set up Linux IPv6 firewall.

Disable unwanted SUID and SGID Binaries

If the SUID/SGID executable faces a security issue or a bug any SEID/SGID enabled file could be misused. Also, any local or remote user could make use of such a file. Finding all such files is then highly recommended. You can use the following command for the same:

- #See all set user id files:
- `find/ -perm +4000`
- # See all group id files
- `find/ -perm +2000`
- # Or combine both in a single command
- `find / \( -perm -4000 -o -perm -2000 \) -print`
- `find / -path -prune -o -type f -perm +6000 -ls`

Use a centralized authentication service

Unless there's a centralized authentication system, user authentication data will become inconsistent. This could lead to out-of-date credentials as well as forgotten accounts that ought to have been deleted. With a centralized authentication service, you can maintain central control over LINUX/ UNIX account and also authentication data. It will also be possible for you to keep authentic data synchronized between multiple servers. Instead of using the NIS service, go for OpenLDAP for clients and servers, if you want to have centralized authentication.

Secure OpenSSH Server

For remote login and file transfer, the SSH protocol is highly effective. But SSH is vulnerable to many type of attacks. So you better make sure that the OpenSSH server is secure.