

Directives and Components are similar:

Both are Angular 2 objects that can modify user interface and correspond to elements in the markup. The selector is used to identify Directive or component that is associated with markup in a template or webpage. For Directives, tag attribute name is used, which utilizes square brackets. Ex- `'[tooltip]'`. For components, tag name is used.

Ex- `'CustomerList'`. Components have `@Component` annotation and Directives have `@Directive` annotation. Both Directives and Components have classes and classes can use Dependency Injection in the same manner through Constructor.

Differences between Directives and Components:

`@Directive` does not require view but `@Component` need view. Directives do not have a template and there is no bundled markup used for element rendering. Directives add behaviour to an existing Document Object Model element.

Types of directives:

1. Component Directives
2. Structural Directives:
 - `NgIf`
 - `NgFor`
 - `NgSwitch`, `NgSwitchWhen`, `NgSwitchDefault`
3. Attribute Directives
 - `NgClass`
 - `NgStyle`
 - `NgControlName`
 - `NgModel`

Steps for creating a directive:

Let us actually understand using this example:

Creating Sizer.ts file-

```
• import {Directive, Component, ElementRef, Renderer} from
  '@angular/core'
• @Directive({selector: '[sizer]'})
• export class Sizer{
•   constructor(element: ElementRef, renderer: Renderer)
•   {renderer.setStyle(element, 'fontSize', 'x-large');}}
```