

The code to update file `sizer.ts` can be found at <http://dgit.in/UpdSizer>. The corresponding explanation is given below.

Explanation:

- Normal imports with 'Input'.
- Use `@Directive` annotation to define the annotation and specify the selector with `[]`.
- Specify the input element value.
- `element: ElementRef` and `renderer: Renderer` are instance variable.
- Constructs an instance of class that uses constructor injection for `ElementRef` and `Renderer` objects which then saves those objects to instance variables for use in method 'ngOnInit'.
- Method 'ngOnInit' is an Angular2 lifecycle method. It is fired automatically once everything is loaded for this component. At this stage `@Input()` `sizer` instance variable has been set by Angular from the attribute value. Now we use the instance variables for the `renderer` and the `element` to set the style for the element from the attribute value plus `x%` on the end. Ex- `200%`.

Based on similar logic, the code to update file `app.ts` can be found at <http://dgit.in/UpdApp>.

Example Code (Directive with Host Events):

Use of directive with mapped inputs and host events. Host events are useful when you need a directive that responds to things happening on the DOM.

For updating file 'hoverer.ts', the code can be found at <http://dgit.in/Upd-Hover>. A new directive has been added in this section. The corresponding explanation can be found below.

Explanation:

- Normal imports with 'Input'
- Use `@Directive` annotation to define the annotation and specify the selector with `[]`.
- Specify inputs.
- Specify host element events.
- `element: ElementRef` and `renderer: Renderer` are instance variable.
- Constructor constructs an instance of the class and uses constructor injection for `ElementRef` and `Renderer` objects. At this stage 'hover' set method has not been called yet.
- Set method for 'hover' input.