

- Methods fired by angular when host events occurs.

In the same way, the code for updating file app.ts with new host events can be found at <http://dgit.in/UpdAppHst>.

Components

A component controls a patch of screen called a view. Angular 2 is also known as component-based framework and is directly inspired by web components. An Angular 2 component and Angular1 controller are similar. A component is basically meta-data, markup and a class (which contains code and data), which is combined together to create a View (UI Widget). By this we can create UI with behaviour. All angular 2 application has root Component which is also known as Application Component. With the help of Angular 2, data can be passed from one component to the other and to respond to each other's events. Angular 2 Component could be considered as Directives of Angular 1 with its own template. You can write a Component and use it as a Child Component in several other Components. They were designed to be self-contained and loosely-coupled for this purpose.

Each Component contains valuable data about itself:

- Input:What data it needs as input.
- What events it may emit to the outside.
- How to draw itself(View).
- Dependencies.

What Does A Component Consist Of?

- Annotation

Provides meta-data to combine all the parts together into a component.

- Template

Usually html markup.Used to render the component in the browser. The View in MVC. Can contain tags for nested components.

- Class

Has annotations to add meta-data. Contains data (was \$scope). Contains code for behavior.

Example:

```
import {Component} from '@angular/core'
@Component({
  selector: 'my-component',
  template: '<div>Hello my name is {{name}}</div>' })
```