

3. Export the class

- `export class AppComponent { }`

The class is exported to make us usable by other parts of the code. After it is exported, it can be simply imported with help of import statement. Functions and variables can be specified inside the class which can be used by Component's template.

Customizing:

Example 1. The code can be found at <http://dgit.in/ExmpleOne>.

Template is modified with added styles property. div with class "parent" is added with static tag. Kindly see next example to pass data dynamically from exported class and access it inside the template.

Nesting the Child Component Inside Parent Component

After creating both the components we need to nest the child component inside the parent component. Following are the 3 changes:

Step 1. Import child component

First we need to import a component before using it.

- `import { ChildComponent } from './child.component';`
`./child.component'` specifies the path of the component.

Step 2 : Add the imported component inside the directives property of AppComponent decorator

- `directives : [ChildComponent]`

Directives property specifies any child component that is used in parent component. In component decorator of AppComponent, directives property is added and assign imported child component.

Step 3 : Use the Child component tag inside parent component template

Modification in parent component:

- `<div class="parent">`
- `<h1>{{name}}</h1>`
- `<child-component></child-component>`
- `</div>`

As this point the updated app.component.ts file should contain the code to be found at <http://dgit.in/UpdAppComp>.

DATABINDING

Databinding played important role to make this framework important.