

For two way data binding and event observation, the code can be found at <http://dgit.in/DataBindTwo>, the output for which shall be as below.

- First Name : Michael
- Last Name : Elango
- Value: Michael Elango
- set name

Two-Way binding :

1. Whenever a user types into the input boxes instance variables (FirstN and LastN) are updated.
2. Updating of the input boxes whenever the code changes the FirstN and LastN variables.

To help understand this, have a look at the code snippets and corresponding explanations below:

1.

- First Name:<input [(ngModel)]="FirstN"/>
-

- Last Name:<input [(ngModel)]="LastN"/>

[HTML markup for 2 fields] with attribute [(ngModel)] = "FirstN". NgModel is a directive that binds a class instance variable to a form control and it is surrounded by two sets of brackets as it is using two way data binding. The [] brackets imply that the bound control get its value from the property in the Class (Model). The () brackets imply event observation. The property in the Model should be updated when user changes bound's control value.

2.

- Value:{{FirstN} {LastN}}

These brackets are used to extract a value from Class(Model) and keep it up to date. This is also known as One Way data binding because it extracts a value from the model but does not change value in the model.

3.

- <button (click)="setName()">set name</button>,

set name is a button with event observation. It calls the setName method when clicked which updates the instance variable.