

Looks to resolve route by name from peer components.	[none]
Looks to resolve route by name from application root (top level).	/
Looks to resolve route by name in current components list of child routes.	./
Looks to resolve route by name in current components parent.	../

Route names

The name of each route, separated by a slash, starting with the top-level route going downwards. For example, if we have a main route 'Other' which has a named route 'Child' inside a subcomponent then the route name will be Other/Child1.

Parameters

Parameters are written up as a JSON object, for example '{subscriberId: 3}'.

Imperative Navigation

Navigation is an asynchronous event and it does not lock the code until it is completed. This is performing navigation in your code. Instead of this the imperative navigation methods return promise object when completed, which is a callback for success or failure. For this router should be injected into your class using Constructor Injections.

1. Router.navigate

Navigate to a component by name. Returns a promise that resolves when navigation is complete. This uses the Link DSL as specified above in Router Link DSL Format. It's basically the same as clicking on a Router Link.

2. Router.navigateByUrl

Navigate to a URL. Returns a promise that resolves when navigation is complete. It's preferred to navigate with navigate instead of this method, since URLs are more brittle. If the given URL begins with a '/', router will navigate absolutely. If the given URL does not begin with '/', the router will navigate relative to this component.

3. Router.navigateByInstruction

Navigate via the provided instruction. Returns a promise that resolves when navigation is complete.