

Such a service when used would not be blocking in case the service logic is slow or requires external responses (XHR etc) to complete.

In most cases server responses for data requests need to return as a promise or an observable which can then be processed with a callback function.

An important point to note is that error handling is highly recommended when using Promises or Observables, the syntax of which would be as follows:

```
• this.myService.serviceMethod().then(/*code to process the
response array*/).catch(function(e) {
  console.log(e);}
```

Built-in Angular 2 Services (Providers)

Angular2 provides a host of useful in built services that can be used to add functionality to your application. Some of the popular ones are listed below:

Http

The Http service class provides functions to make http calls that are serviced by the XMLHttpRequest [httpBackend](#) (ignore this jargon for now). Simply put, it allows your application to make http calls for external information like resources, data or actions using REST. This is incredibly useful as most angular applications would be communicating with a backend server for data exchange and actions, and the easiest way of doing this would be to make http calls to the server.

However it is important to note that the http service does not ship directly with the core angular package but as part of an optional module `@angular/http`. Let us take a moment to look at the syntax for the http service functions.

```
• get(url: string, options?: RequestOptionsArgs) :
Observable<Response>
• Performs a request with get http method.
• post(url: string, body: any, options?: RequestOptionsArgs)
: Observable<Response>
• Performs a request with post http method.
• put(url: string, body: any, options?: RequestOptionsArgs)
: Observable<Response>
• Performs a request with put http method.
• delete(url: string, options?: RequestOptionsArgs) :
Observable<Response>
• Performs a request with delete http method.
```