

- `patch(url: string, body: any, options?: RequestOptionsArgs) : Observable<Response>`
- Performs a request with patch http method.
- `head(url: string, options?: RequestOptionsArgs) : Observable<Response>`
- Performs a request with head http method.
- `options(url: string, options?: RequestOptionsArgs) : Observable<Response>`
- Performs a request with options http method.

Notice that the method signatures mimic the type of requests possible using the Http protocol (nearly, since patch is actually yet to be a standard), and that they all return an Observable of type response.



Animate

Animate service specifies an animation step that will apply the provided styles data for a given amount of time based on the provided timing expression value. Calls to animate are expected to be used within an animation sequence, group, or transition.

http calls are made through the built-in HTTP service

- `animate(timing: string | number, styles?: AnimationStyleMetadata | AnimationKeyframesSequenceMetadata) : AnimationAnimateMetadata`

The animate function accepts two input parameters: timing and styles:

- **timing** is a string based value that can be a combination of a duration with optional delay and easing values. The format for the expression breaks down to `duration delay easing` (therefore a value such as `1s 100ms ease-out` will parse itself into `duration=1000, delay=100, easing=ease-out`).
- **styles** is the style input data which can either be a call to style or keyframes. If left empty then the styles from the destination state will be collected and used.