

Location

Location is a service that applications can use to interact with a browser's URL. Depending on which `LocationStrategy` is used, Location will either persist to the URL's path or the URL's hash segment.

Location is responsible for normalizing the URL against the application's base href. A normalized URL is absolute from the URL host, includes the application's base href, and has no trailing slash:

- `/my/app/user/123` is normalized
- `my/app/user/123` is not normalized
- `/my/app/user/123/` is not normalized

Note: it's better to use Router service to trigger route changes. Use Location only if you need to interact with or create normalized URLs outside of routing.

Available methods in location service:

- `path(includeHash?: boolean) : string`

Returns the normalized URL path.

- `isCurrentPathEqualTo(path: string, query?: string) : boolean`

Normalizes the given path and compares to the current normalized path.

- `normalize(url: string) : string`

Given a string representing a URL, returns the normalized URL path without leading or trailing slashes.

- `prepareExternalUrl(url: string) : string`

Given a string representing a URL, returns the platform-specific external URL path. If the given URL doesn't begin with a leading slash ('/'), this method adds one before normalizing. This method will also add a hash if `HashLocationStrategy` is used, or the `APP_BASE_HREF` if the `PathLocationStrategy` is in use.

- `go(path: string, query?: string) : void`

Changes the browser's URL to the normalized version of the given URL, and pushes a new item onto the platform's history.

- `replaceState(path: string, query?: string) : void`



The location service is used to interact with the browser URL